April 15, 2005

Mr. Noman Chowdhury California Regional Water Quality Control Board Los Angeles Region 320 West 4th Street, Suite 200 Los Angeles, California 90013

Subject:

Quarterly Report for the First Quarter 2005

Mobil Station 18MLJ

5005 North Long Beach Boulevard

Long Beach, California

CRWQCB Case No. 908050452A

Mr. Chowdhury:

At the request of ExxonMobil Oil Corporation (ExxonMobil), formerly Exxon Company, U.S.A., Environmental Resolutions, Inc. is submitting the First Quarter 2005 ExxonMobil Quarterly Report for the above-referenced site. The format utilized for the report consolidates groundwater sampling (where applicable), Title 23, Subchapter 16 reporting and consultant progress updates for ExxonMobil into one summary report.

Please call me at (949) 457-8954 if you have any questions.

Sincerely,

Environmental Resolutions, Inc.

George E. Salley

Senior Project Geologist

P.G. 6308

Cc: Ms. Marla D. Guensler, ExxonMobil

Ms. Carmen Piro, Long Beach Department of Health and Human Services

ERI 316313NC.105

3163 EXNQTRLY

Date: <u>April 15, 2005</u>

Site Status: Active Mobil Station

Station Number: <u>18MLJ</u> Address:

ExxonMobil Environmental Engineer: Consulting Company/Contact Person:

Other Agencies to Receive Copies:

Daine and American

Primary Agency:

5005 North Long Beach Boulevard, Long Beach, CA

Ms. Marla D. Guensler

Environmental Resolutions, Inc. (ERI)/George E. Salley

Mr. Noman Chowdhury, California Regional Water Quality Control Board - Los Angeles Region (CRWQCB)

320 West 4th Street, Suite 200, Los Angeles, CA 90013

Ms. Carmen Piro

EXXONMOBIL OIL CORPORATION (EXXONMOBIL)

QUARTERLY REPORT

Long Beach Department of Health and Human Services

2525 Grand Avenue, Long Beach, CA 90815

WORK PERFORMED THIS QUARTER [First - 2005]:

- o 01/14/05 Submitted the quarterly report for the fourth quarter 2004.
- o 02/25/05 ERI received a copy of the CRWQCB letter approving the site assessment to install three off-site groundwater monitoring wells. The letter was sent to ExxonMobil and was dated 11/30/04. The approval letter also mandated the installation of one additional groundwater monitoring well in the northeastern portion of the site.
- o 03/04/05 ExxonMobil submitted an interim remedial action plan (IRAP), prepared by ERI, for an air sparge/soil vapor extraction (AS/SVE) feasibility study to be conducted at the site. The IRAP included the details associated with the drilling and construction of four AS/SVE wells to be utilized during the feasibility study.
- o 03/16/05 ERI, on behalf of ExxonMobil, directed the drilling and sampling of soil boring B7, in accordance with the CRWQCB requirement. The soil boring was completed as groundwater monitoring well MW7. During this investigation, groundwater was encountered at approximately 30 feet below ground surface (bgs). The groundwater monitoring well was completed to a total depth of 51.5 feet bgs, and with a 30-foot screened interval.
- o 03/21/05 Performed quarterly purge groundwater monitoring and sampling. Properly recycled purge water at Crosby & Overton of Long Beach, California, under a non-hazardous waste manifest. The manifest will be included with the second quarter 2005 quarterly report.

WORK PROPOSED FOR NEXT QUARTER [Second - 2005]:

- Perform quarterly purge groundwater monitoring and sampling.
- o Submit a quarterly report.
- o Conduct the AS/SVE feasibility study as presented in the IRAP.

Current Phase of Project:
Frequency of Monitoring and Sampling:
Is LPH Present on Site:
Cumulative LPH Recovered to Date:
Water Wells or Surface Waters within 1000'
& Their Respective Directions:
Permits for Discharge:
Current Remediation Techniques:
Depth to Groundwater:

| Monitoring and sampling | |
|--|---|
| Quarterly | |
| No | - |
| None | _ |
| | |
| None | |
| NA | |
| None | |
| 27 to 29 feet bgs - measured on 03/21/05 | |

Please call Mr. George E. Salley at (949) 457-8954 for any questions regarding this report.



Respectfully Submitted, Environmental Resolutions, Inc.

George E. Solley

George E. Salley Senior Project Geologist P.G. 6308

ATTACHED:

- o Site Location Map (Plate 1)
- o Groundwater Contour Map 03/21/05 (Plate 2)
- o Groundwater Sample Analyses Map 03/21/05 (Plate 3)
- o Cumulative Water Level Measurements and Groundwater Analyses (Table 1)
- o Laboratory Report and Chain-of-Custody Record
- o Purging and Sampling Records
- o Purging and Sampling Protocol

Current Phase of Project:
Frequency of Monitoring and Sampling:
Is LPH Present on Site:
Cumulative LPH Recovered to Date:
Water Wells or Surface Waters within 1000'
& Their Respective Directions:
Permits for Discharge:
Current Remediation Techniques:
Depth to Groundwater:

| Monitoring and sampling | |
|--|--|
| Quarterly | |
| No | |
| None | |
| | |
| None | |
| NA | |
| None | |
| 27 to 29 feet bgs - measured on 03/21/05 | |

Please call Mr. George E. Salley at (949) 457-8954 for any questions regarding this report.




Respectfully Submitted, Environmental Resolutions, Inc.

George E. Solley

George E. Salley Senior Project Geologist P.G. 6308

ATTACHED:

- o Site Location Map (Plate 1)
- o Groundwater Contour Map 03/21/05 (Plate 2)
- o Groundwater Sample Analyses Map 03/21/05 (Plate 3)
- o Cumulative Water Level Measurements and Groundwater Analyses (Table 1)
- o Laboratory Report and Chain-of-Custody Record
- o Purging and Sampling Records
- o Purging and Sampling Protocol




FN 3163TOPO

EXPLANATION



1/2-mile radius circle

APPROXIMATE SCALE



SOURCE: Modified from a map provided by National Geographic's TOPO!



SITE LOCATION MAP


MOBIL STATION 18MLJ 5005 North Long Beach Boulevard Long Beach, California


PROJECT NO.

3163

PLATE

1





CUMULATIVE WATER LEVEL MEASUREMENTS AND GROUNDWATER ANALYSES

MOBIL STATION 18MLJ

5005 NORTH LONG BEACH BOULEVARD

LONG BEACH, CALIFORNIA

ERI 3163

| Date | Well Elev | GW Depth | GW Elev | LPH | Benzene (ug/l) | Toluene (ug/l) | Ethyl- benzene (ug/l) | Xylenes (ug/l) | TPHg (ug/l) | TPHd (ug/l) | TRPH (ug/l) | MTBE (ug/l) | DIPE (ug/l) | ETBE (ug/l) | TAME (ug/l) | TBA (ug/l) | Ethanol (ug/l) | Methanol (ug/l) |
|-------------|-----------|----------|---------|------|-------------------|-------------------|-----------------------------|-------------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|---------------|-------------------|--------------------|
| Field Point | DAVASA | | | | (ug/i) | | (<i>ug/i)</i> | (<i>uyn)</i> | (ug/i) | (ug/i) | (ug/i) | (ug/i) |
| 4/17/2003 | 41.10 | 29.66 | 11.44 | no | <1.00 | <1.00 | <1.00 | <1.00 | 230 | 133 | <100 | <2.00 | <1.00 | <1.00 | <1.00 | <10.0 | <1000 | <10000 |
| 3/26/2003 | 41.10 | 29.52 | 11.58 | | <1.00 | <1.00 | <1.00 | <1.00 | 97.4 | <500 | | | | <i>-</i> | | | | |
| 0/20/2003 | 41.10 | 29.52 | | no | ~1.00 | <1.00 | <1.00 | ~1.00 | 97.4 | \ 000 | | <2.00 | <1.00 | <1.00 | <1.00 | <10.0 | <1000 | <10000 |
| 11/14/2003 | 41.10 | 29.88 | 11.22 | no | <1.00 | <1.00 | <1.00 | <1.00 | <50.0 | <500 | | <2.00 | <1.00 | <1.00 | <1.00 | <10.0 | | |
| 2/21/2004 | 41.10 | 30.03 | 11.07 | no | <1.00 | <1.00 | <1.00 | <1.00 | <50.0 | <500 | | <2.00 | <1.00 | <1.00 | <1.00 | <10.0 | <1000 | <10000 |
| 4/30/2004 | 41.10 | 29.85 | 11.25 | no | <1.00 | <1.00 | <1.00 | <1.00 | <50.0 | <500 | | <2.00 | <1.00 | <1.00 | <1.00 | 69.0 | | |
| 7/10/2004 | 41.10 | 30.50 | 10.60 | no | <1.00 | <1.00 | <1.00 | <1.00 | 231 | <500 | | 2.90 | <1.00 | <1.00 | <1.00 | <10.0 | | |
| 11/5/2004 | 41.10 | 30.52 | 10.58 | no . | <1.00 | <1.00 | <1.00 | <1.00 | <50.0 | <500 | | <2.00 | <1.00 | <1.00 | <1.00 | <10.0 | | |
| 3/21/2005 | 41.10 | 29.21 | 11.89 | no | 0.70 | <0.50 | 0.60 | 3.40 | <50.0 | <500 | · ······· | 6.10 | <1.00 | <1.00 | 1.00 | 17.0 | <200 | <5000 |
| Field Point | MW2 | | | | | | | | | | | | | | | | | |
| 4/17/2003 | 39.55 | 28.43 | 11.12 | no | 5.90 | 3660 | 1340 | 3940 | 19900 | 2980 | <100 | 131 | <1.00 | <1.00 | <1.00 | <10.0 | <1000 | <10000 |
| 3/26/2003 | 39.55 | 28.31 | 11.24 | no | 118 | 1220 | 1260 | 625 | 15600 | 1490 | | 5200 | <1.00 | <1.00 | 5.70 | 85.1 | <1000 | <10000 |
| 11/14/2003 | 39.55 | 28.66 | 10.89 | no | 68.0 | 1280 | 1280 | 770 | 9810 | 1110 | | 4260 | <1.00 | <1.00 | <1.00 | 142 | | |
| 2/21/2004 | 39.55 | 28.82 | 10.73 | no | 47.1 | 560 | 1220 | 775 | 10600 | 1710 | | 975 | <1.00 | <1.00 | <1.00 | 56.5 | <1000 | <10000 |
| 4/30/2004 | 39.55 | 28.62 | 10.93 | no | 61.0 | 424 | 1390 | 550 | 9090 | 872 | | 1040 | <1.00 | <1.00 | <1.00 | <10.0 | | |
| 7/10/2004 | 39.55 | 29.34 | 10.21 | no | 60.4 | 348 | 1260 | 402 | 8260 | 1220 | | 920 | <1.00 | <1.00 | <1.00 | 125 | | |
| 11/5/2004 | 39.55 | 29.31 | 10.24 | no | 66.7 | 238 | 930 | 190 | 6360 | 878 | | 220 | <1.00 | <1.00 | <1.00 | <10.0 | | |
| 3/21/2005 | 39.55 | 27.96 | 11.59 | no | 80.7 | 125 | 538 | 90.1 | 2670 | <500 | | 1370 | <1.00 | 0.60 J | 0.70 J | 522 | <200 | <5000 |
| Field Point | MW3 | | | | | | | | | | | | | | | | | |
| 4/17/2003 | 40.84 | 29.34 | 11.50 | no | <1.00 | <1.00 | 1.50 | 7.70 | 2530 | 916 | <100 | 105 | <1.00 | <1.00 | <1.00 | 45.4 | <1000 | <10000 |
| 3/26/2003 | 40.84 | 29.26 | 11.58 | no | <1.00 | <1.00 | 1.60 | <1.00 | 162 | <500 | | 112 | <1.00 | <1.00 | <1.00 | <10.0 | <1000 | <10000 |

CUMULATIVE WATER LEVEL MEASUREMENTS AND GROUNDWATER ANALYSES

MOBIL STATION 18MLJ

5005 NORTH LONG BEACH BOULEVARD

LONG BEACH, CALIFORNIA

ERI 3163

| Date | Well Elev | GW Depth | GW Elev | LPH | Benzene (ug/l) | Toluene (ug/l) | Ethyl- benzene (ug/l) | Xylenes (ug/l) | TPHg (ug/l) | TPHd (ug/l) | TRPH (ug/l) | MTBE (ug/l) | DIPE (ug/l) | ETBE (ug/l) | TAME (ug/l) | TBA (ug/l) | Ethanol (ug/l) | Methanol (ug/l) |
|-------------|------------|----------|---------|---|-------------------|-------------------|-----------------------------|-------------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|---------------|-------------------|--|
| 11/14/2003 | 40.84 | 29.57 | 11.27 | no | <1.00 | <1.00 | 2.40 | <1.00 | 179 | <500 | | 87.2 | <1.00 | <1.00 | <1.00 | <10.0 | | |
| 2/21/2004 | 40.84 | 29.73 | 11.11 | по | 1.20 | <1.00 | 2.30 | <1.00 | 170 | <500 | | 116 | <1.00 | <1.00 | <1.00 | <10.0 | <1000 | <10000 |
| 4/30/2004 | 40.84 | 29.57 | 11.27 | no | <1.00 | <1.00 | 2.00 | 6.40 | 138 | <500 | | 137 | <1.00 | <1.00 | <1.00 | <10.0 | | |
| 7/10/2004 | 40.84 | 30.31 | 10.53 | no | <1.00 | <1.00 | 2.80 | <1.00 | 139 | <500 | | 89.6 | <1.00 | <1.00 | <1.00 | <10.0 | | |
| 11/5/2004 | 40.84 | 30.25 | 10.59 | no | 1.50 | <1.00 | 4.30 | <1.00 | 181 | <500 | | 182 | <1.00 | <1.00 | <1.00 | 50.3 | | |
| 3/21/2005 | 40.84 | 28.88 | 11.96 | no | 2.60 | <0.50 | 1.20 | 1.00 | 222 | <500 | | 120 | <1.00 | <1.00 | <1.00 | 97.4 | <200 | <5000 |
| Field Point | MW4 | | | | | | | | | | | | | | | - | | |
| 11/5/2004 | 39.10 | 30.85 | 8.25 | no | 23.7 | <1.00 | <1.00 | <1.00 | 247 | <500 | | 27.1 | <1.00 | <1.00 | <1.00 | 5760 | | |
| 3/21/2006 | 39.10 | 27.51 | 11.59 | no | 35.6 | <0.50 | 0.90 | 13.8 | 2060 | 831 | | 76.6 | <1.00 | 1.20 | 1.10 | 49700 | <200 | 1800 J |
| Field Point | MW5 | | | | | | | | | | | | | | | | | |
| 11/5/2004 | 38.72 | 28.74 | 9.98 | no | <1.00 | 119 | 280 | 900 | 6520 | 1330 | | <2.00 | <1.00 | <1.00 | <1.00 | <10.0 | | |
| 3/21/2005 | 38.72 | 27.39 | 11.33 | no | 23.1 | <0.50 | 8.10 | 1.40 | 1420 | 560 | | 9.70 | <1.00 | <1.00 | <1.00 | 5250 | <200 | <5000 |
| Field Point | MW6 | N | | | | | | | | | | | | | | | | - W - 11 - 12 - 12 - 12 - 12 - 12 - 12 - |
| 11/5/2004 | 39.21 | 29.11 | 10.10 | no | 3.50 | 5.00 | 1120 | 404 | 8090 | 1580 | | <2.00 | <1.00 | <1.00 | <1.00 | <10.0 | | |
| 3/21/2005 | 39.21 | 27.76 | 11.45 | no | <0.50 | <0.50 | 585 | 122 | 3960 | 749 | | <1.00 | <1.00 | <1.00 | <1.00 | <50.0 | <200 | 1200 J |
| Field Point | MW7 | | | | | | | | | | | | | | - | | | |
| 3/21/2005 | 41.14 | 29.09 | 12.05 | no | <0.50 | <0.50 | <0.50 | <0.50 | <50.0 | <500 | | 0.50 J | <1.00 | <1.00 | <1.00 | 4.70 J | <200 | <5000 |
| Field Point | Trip Blank | | | | ***** | | | | | | | | | | | | | |
| 4/17/2003 | | | | no | <1.00 | <1.00 | <1.00 | <1.00 | <50.0 | | | <2.00 | <1.00 | <1.00 | <1.00 | <10.0 | <1000 | <10000 |
| 8/26/2003 | | | | no | <1.00 | <1.00 | <1.00 | <1.00 | <50.0 | 7111 da anti- | | <2.00 | <1.00 | <1.00 | <1.00 | <10.0 | hada | |
| 11/14/2003 | | | | no | <1.00 | <1.00 | <1.00 | <1.00 | <50.0 | | | <2.00 | <1.00 | <1.00 | <1.00 | <10.0 | | |
| 2/21/2004 | | | | no | <1.00 | <1.00 | <1.00 | <1.00 | <50.0 | | | <2.00 | <1.00 | <1.00 | <1.00 | <10.0 | | |
| | | | | ***** ********************************* | | | | , | | | | | | | | | | |

CUMULATIVE WATER LEVEL MEASUREMENTS AND GROUNDWATER ANALYSES

MOBIL STATION 18MLJ

5005 NORTH LONG BEACH BOULEVARD

LONG BEACH, CALIFORNIA

ERI 3163

| Date | Well Elev GW Depth | LPH | Benzene (ug/l) | Toluene (ug/l) | Ethyl- benzene (ug/l) | Xylenes (ug/l) | TPHg (ug/l) | TPHd (ug/l) | TRPH (ug/l) | MTBE (ug/l) | DIPE (ug/l) | ETBE (ug/l) | TAME (ug/l) | TBA (ug/l) | Ethanol (ug/l) | Methanol (ug/l) |
|-----------|--------------------|--------|-------------------|-------------------|-----------------------------|-------------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|---------------|-------------------|--------------------|
| 4/30/2004 | | no | <1.00 | 1.00 | <1.00 | <1.00 | <50.0 | | | <2.00 | <1.00 | <1.00 | <1.00 | <10.0 | | |
| 7/10/2004 | | no | <1.00 | <1.00 | <1.00 | <1.00 | 50.0 | | | <2.00 | <1.00 | <1.00 | <1.00 | <10.0 | | |
| 11/5/2004 | | no | <1.00 | <1.00 | <1.00 | <1.00 | <50.0 | | | <2.00 | <1.00 | <1.00 | <1.00 | <10.0 | | |
| 3/21/2005 | | no | <0.50 | <0.50 | <0.50 | <0.50 | <50.0 | | | <1.00 | <1.00 | <1.00 | <1.00 | <10.0 | | |

CUMULATIVE WATER LEVEL MEASUREMENTS AND GROUNDWATER ANALYSES MOBIL STATION 18MLJ 5005 NORTH LONG BEACH BOULEVARD LONG BEACH, CALIFORNIA

ERI 3163

Explanation:

ELEV = elevation

EPA = Environmental Protection Agency

GW = groundwater

DIPE = di-isopropyl ether

ETBE = ethyl tertiary butyl ether
TAME = tertiary amyl methyl ether
TBA = tertiary butyl alcohol
TPHd = total petroleum hydrocarbons as diesel

TPHg = total petroleum hydrocarbons as gasoline TRPH = total recoverable petroleum hydrocarbons

MTBE = methyl tertiary butyl ether
MTBE analyzed by EPA Method 8260B.
LPH = liquid phase hydrocarbons (thickness measured in feet)

J = estimated value between method detection limit and practical quantification limit

<10000 = not detected at or above stated laboratory reporting limit

ug/l = micrograms per liter



4/11/05

ENVIRONMENTAL RESOLUTIONS, INC 10203
GEORGE SALLEY
20372 NORTH SEA CIRCLE
LAKE FOREST, CA 92630

This report includes the analytical certificates of analysis for all samples listed below. These samples relate to your project identified below:

Project Number: ERI 3163 13.

Laboratory Project Number: 410354.

An executed copy of the chain of custody, the project quality control data, and the sample receipt form are also included as an addendum to this report. Any QC recoveries outside laboratory control limits are flagged individually with an #. Sample specific comments and quality control statements are included in the Laboratory notes section of the analytical report for each sample report. If you have any questions relating to this analytical report, please contact your Laboratory Project Manager at 1-800-765-0980. Any opinions, if expressed, are outside the scope of the Laboratory's accredidation.

| | | Page 1 |
|-----------------------|------------|-----------------|
| Sample Identification | Lab Number | Collection Date |
| | | |
| • | | |
| W-29-MW7 | 05-A41294 | 3/21/05 |
| W-29-MW1 | 05-A41295 | 3/21/05 |
| W-28-MW3 | 05-A41296 | 3/21/05 |
| W-27-MW4 | 05-A41297 | 3/21/05 |
| W-27-MW2 | 05-A41298 | 3/21/05 |
| W-27-MW5 | 05-A41299 | 3/21/05 |
| W-27-MW6 | 05-A41300 | 3/21/05 |
| TRIP BLANKS | 05-A41301 | 3/21/05 |



2960 Foster Creighton Drive • Nashville, Tennessee 37204
800-765-0980 • 615-726-3404 Fax

Sample Identification

Lab Number

Collection Date

These results relate only to the items tested. This report shall not be reproduced except in full and with permission of the laboratory.

Report Approved By:

Report Date: 4/ 1/05

Johnny A. Mitchell, Laboratory Director Michael H. Dunn, M.S., Technical Director Pamela A. Langford, Senior Project Manager Eric S. Smith, QA/QC Director

Gail A. Lage, Senior Project Manager Glenn L. Norton, Technical Services Kelly S. Comstock, Technical Services Roxanne L. Connor, Senior Project Manager

Laboratory Certification Number: 01168CA

This material is intended only for the use of the individual(s) or entity to whom it is addressed, and may contain information that is privileged and confidential. If you are not the intended recipient, or the employee or agent responsible for delivering this material to the intended recipient, you are hereby notified that any dissemination, distribution, or copying of this material is strictly prohibited. If you have received this material in error, please notify us immediately at 615-726-0177.



ANALYTICAL REPORT

ENVIRONMENTAL RESOLUTIONS, INC 10203

GEORGE SALLEY

20372 NORTH SEA CIRCLE LAKE FOREST, CA 92630

Project: ERI 3163 13

Project Name: EXXONMOBIL 18-MLJ

Sampler: JAMES CAVERS

Purchase Order: 4506125986

Lab Number: 05-A41294 Sample ID: W-29-MW7 Sample Type: Water

Site ID: 18-MLJ

Date Collected: 3/21/05

Time Collected: 14:40

Date Received: 3/23/05 Time Received: 7:50

| Parameter | Result Flag | Limit of Units Quantitation | Limit of Dilution Detection Factor | Date Ti | ime Method | Analyst Batch |
|--------------------------|-------------|-----------------------------|------------------------------------|------------|-------------------|-----------------|
| **Volatile Organics | | | | | | |
| **Ethyl-t-butylether | <1.00 | ug/l 1.00 | 0.27 1. | 3/25/05 14 | 1:56 8260B | S. Edwards 2734 |
| **tert-amyl methyl ether | <1.00 | ug/L 1.00 | 0.30 1. | 3/25/05 14 | 1:56 8260B | S. Edwards 2734 |
| **Tertiary butyl alcohol | 4.70 J | ug/l 10.0 | 4.28 1.0 | 3/25/05 14 | 1:56 8260B | S. Edwards 2734 |
| **Benzene | <0.50 | ug/l 0.50 | 0.25 1. | 3/25/05 14 | 1:56 8260B | S. Edwards 2734 |
| **Ethylbenzene | <0.50 | ug/l 0.50 | 0.19 1. | 3/25/05 14 | 1:56 8260B | S. Edwards 2734 |
| **Toluene | <0.50 | ug/l 0.50 | 0.17 1. | 3/25/05 14 | 1:56 8260B | S. Edwards 2734 |
| **Xylenes (Total) | <0.50 | ug/l 0.50 | 0.33 1. | 3/25/05 14 | 1:56 8260B | S. Edwards 2734 |
| **Methyl-t-butyl ether | 0.50 J | ug/l 1.00 | 0.23 1.0 | 3/25/05 14 | 1:56 8260B | S. Edwards 2734 |
| Ethanol | <200. | ug/L 200. | 30.7 1. | 3/25/05 14 | 1:56 8260B | S. Edwards 2734 |
| **Diisopropyl ether | <1.00 | ug/l 1.00 | 0.18 1. | 3/25/05 14 | 1:56 8260/SA05-77 | S. Edwards 2734 |
| **Methanol | <5000 | ug/l 5000 | 160 1. | 3/30/05 13 | 3:49 8015B | K. Roberso 2765 |
| **TPH-GC | | | | | | |
| **TPH (Gasoline Range) | <50.0 | ug/l 50.0 | 33.0 1. | 3/29/05 20 | :15 CA-LUFT | A. Cobbs 4812 |

33.

1.

3/30/05 11:05 8015B/CA-LUFTB. Yanna

Sample Extraction Data

**TPH (Diesel Range,C13-C22) <500.

| | Wt/Vol | | | | | |
|-----------|-----------|-------------|---------|------|----------|--------|
| Parameter | Extracted | Extract Vol | Date | Time | Analyst | Method |
| | | | | | | |
| TPH-D | 1000 m | ıl 1.00 ml | 3/28/05 | 9:15 | J. Davis | 3510 |

ug/l

500.



ANALYTICAL REPORT

Laboratory Number: 05-A41294

Sample ID: W-29-MW7

Page 2

| Surrogate | % Recovery | Target Range |
|---------------------------|------------|--------------|
| | | |
| TPH Hi Surr., o-Terphenyl | 125. | 55 133. |
| BTEX/GRO Surr., a,a,a-TFT | . 88. | 69 132. |
| GC FID Surrogate | 70.0 | 50 150. |
| VOA Surr 1,2-DCA-d4 | 80. | 73 127. |
| VOA Surr Toluene-d8 | 98. | 79 113. |
| VOA Surr, 4-BFB | 98. | 79 125. |
| VOA Surr, DBFM | 95. | 75 134. |
| | | |

- ND = Not detected at the limit of Quantitation.
- U = Analyte analyzed for but not detected.
- # = Recovery outside Laboratory historical or method prescribed limits.
- ${\tt J}$ = All results evaluated to the Limit of Detection for reporting. Values below the Limit of Quantitation but above the Limit of Detection are qualified with ${\tt J}$ as estimated.
- B = Analyte was detected in the method blank.
- E = Estimated Value above the calibration limit of the instrument.



ANALYTICAL REPORT

ENVIRONMENTAL RESOLUTIONS, INC 10203

GEORGE SALLEY

20372 NORTH SEA CIRCLE LAKE FOREST, CA 92630

Project: ERI 3163 13

Project Name: EXXONMOBIL 18-MLJ

Sampler: JAMES CAVERS

Lab Number: 05-A41295 Sample ID: W-29-MW1

Sample Type: Water Site ID: 18-MLJ

Date Collected: 3/21/05

Time Collected: 14:30

Date Received: 3/23/05

Time Received: 7:50

Purchase Order: 4506125986

| Parameter | Result | Flag Units | Limit of Quantitation | Limit of Detection | | Date | Time | Method | Analys | t B | Batch |
|------------------------------|--------|------------|-----------------------|-----------------------|-----|---------|-------|--------------|----------|------|-------|
| | | | | | | | | | | | |
| **Volatile Organics | | | | | | | | | | | |
| **Ethyl-t-butylether | <1.00 | ug/l | 1.00 | 0.27 | 1. | 3/25/05 | 15:19 | 8260B | S. Edw | ards | 2734 |
| **tert-amyl methyl ether | 1.00 | ug/L | 1.00 | 0.30 | 1.0 | 3/25/05 | 15:19 | 8260B | S. Edw | ards | 2734 |
| **Tertiary butyl alcohol | 17.0 | ug/l | 10.0 | 4.28 | 1.0 | 3/25/05 | 15:19 | 8260B | S. Edw | ards | 2734 |
| **Benzene | 0.70 | ug/1 | 0.50 | 0.25 | 1.0 | 3/25/05 | 15:19 | 8260B | S. Edw | ards | 2734 |
| **Ethylbenzene | 0.60 | ug/l | 0.50 | 0.19 | 1.0 | 3/25/05 | 15:19 | 8260B | S. Edwa | ards | 2734 |
| **Toluene | <0.50 | ug/l | 0.50 | 0.17 | 1. | 3/25/05 | 15:19 | 8260B | S. Edwa | ards | 2734 |
| **Xylenes (Total) | 3.40 | ug/1 | 0.50 | 0.33 | 1.0 | 3/25/05 | 15:19 | 8260B | S. Edwa | ards | 2734 |
| **Methyl-t-butyl ether | 6.10 | ug/l | 1.00 | 0.23 | 1.0 | 3/25/05 | 15:19 | 8260B | S. Edwa | ards | 2734 |
| Ethanol | <200. | ug/L | 200. | 30.7 | 1. | 3/25/05 | 15:19 | 8260B | S. Edwa | ards | 2734 |
| **Diisopropyl ether | <1.00 | ug/1 | 1.00 | 0.18 | 1. | 3/25/05 | 15:19 | 8260/SA05-77 | S. Edwa | ards | 2734 |
| **Methanol | <5000 | ug/l | 5000 | 160 | 1. | 3/30/05 | 13:55 | 8015B | K. Rob | erso | 2765 |
| **TPH-GC | | | | | | | • | | | | |
| **TPH (Gasoline Range) | <50.0 | ug/l | 50.0 | 33.0 | 1. | 3/29/05 | 20:49 | CA-LUFT | A. Cob | os | 4812 |
| **TPH (Diesel Range,C13-C22) | <500. | ug/l | 500. | 33. | 1. | 3/30/05 | 11:25 | 8015B/CA-LUF | TB. Yanı | na | 4925 |
| | | | | | | | | | | | |

Sample Extraction Data

| | Wt/Vol | | | | | |
|-----------|-----------|-------------|---------|------|----------|--------|
| Parameter | Extracted | Extract Vol | Date | Time | Analyst | Method |
| | | | | | | |
| TPH-D | 1000 m | l 1.00 ml | 3/28/05 | 9:15 | J. Davis | 3510 |



ANALYTICAL REPORT

Laboratory Number: 05-A41295

Sample ID: W-29-MW1

Page 2

| Surrogate | % Recovery | Target Range |
|---------------------------|------------|--------------|
| | , | |
| | | |
| TPH Hi Surr., o-Terphenyl | 75. | 55 133. |
| BTEX/GRO Surr., a,a,a-TFT | 91. | 69 132. |
| GC FID Surrogate | 53.0 | 50 150. |
| VOA Surr 1,2-DCA-d4 | 81. | 73 127. |
| VOA Surr Toluene-d8 | 100. | 79 113. |
| VOA Surr, 4-BFB | 97. | 79 125. |
| VOA Surr, DBFM | 100. | 75 134. |

- ND = Not detected at the limit of Quantitation.
- U = Analyte analyzed for but not detected.
- # = Recovery outside Laboratory historical or method prescribed limits.
- ${\tt J}$ = All results evaluated to the Limit of Detection for reporting. Values below the Limit of Quantitation but above the Limit of Detection are qualified with ${\tt J}$ as estimated.
- B = Analyte was detected in the method blank.
- E = Estimated Value above the calibration limit of the instrument.



ANALYTICAL REPORT

ENVIRONMENTAL RESOLUTIONS, INC 10203

GEORGE SALLEY

20372 NORTH SEA CIRCLE LAKE FOREST, CA 92630

Project: ERI 3163 13

Project Name: EXXONMOBIL 18-MLJ

Sampler: JAMES CAVERS

Lab Number: 05-A41296 Sample ID: W-28-MW3

Sample Type: Water Site ID: 18-MLJ

Date Collected: 3/21/05

Time Collected: 14:50

Date Received: 3/23/05 Time Received: 7:50

Purchase Order: 4506125986

| Parameter | Result | Flag | Units | Limit of Quantitation | Limit of Detection | Date | Time | Method | Analyst | Batch |
|---------------------|--------|------|-------|--------------------------|-----------------------|------|------|--------|---------|-------|
| | | | | | | | | | | |
| **Volatile Organics | | | | | | | | | | |

| **Ethyl-t-butylether | <1.00 | ug/l | 1.00 | 0.27 | 1. | 3/25/05 | 15:41 | 8260B | s. | Edwards | 2734 |
|--------------------------|-------|------|------|------|-----|---------|-------|--------------|----|---------|------|
| **tert-amyl methyl ether | <1.00 | ug/L | 1.00 | 0.30 | 1. | 3/25/05 | 15:41 | 8260B | s. | Edwards | 2734 |
| **Tertiary butyl alcohol | 97.4 | ug/l | 10.0 | 4.28 | 1.0 | 3/25/05 | 15:41 | 8260B | s. | Edwards | 2734 |
| **Benzene | 2.60 | ug/l | 0.50 | 0.25 | 1.0 | 3/25/05 | 15:41 | 8260B | s. | Edwards | 2734 |
| **Ethylbenzene | 1.20 | ug/l | 0.50 | 0.19 | 1.0 | 3/25/05 | 15:41 | 8260B | s. | Edwards | 2734 |
| **Toluene | <0.50 | ug/l | 0.50 | 0.17 | 1. | 3/25/05 | 15:41 | 8260B | s. | Edwards | 2734 |
| **Xylenes (Total) | 1.00 | ug/l | 0.50 | 0.33 | 1.0 | 3/25/05 | 15:41 | 8260B | s. | Edwards | 2734 |
| **Methyl-t-butyl ether | 120. | ug/l | 1.00 | 0.23 | 1.0 | 3/25/05 | 15:41 | 8260B | s. | Edwards | 2734 |
| Ethanol | <200. | ug/L | 200. | 30.7 | 1. | 3/25/05 | 15:41 | 8260B | s. | Edwards | 2734 |
| **Diisopropyl ether | <1.00 | ug/l | 1.00 | 0.18 | 1. | 3/25/05 | 15:41 | 8260/SA05-77 | s. | Edwards | 2734 |
| **Methanol | <5000 | ug/l | 5000 | 160 | 1. | 3/30/05 | 14:01 | 8015B | к. | Roberso | 2765 |
| | | | | | | | | | | | |

**TPH-GC

| **TPH (Gasoline Range) | 222. | ug/l | 50.0 | 33.0 | 1.0 | 3/29/05 | 21:24 | CA-LUFT F | A. Cobbs | 4812 |
|------------------------------|-------|------|------|------|-----|---------|-------|----------------|----------|------|
| **TPH (Diesel Range,C13-C22) | <500. | ug/l | 500. | 33. | 1. | 3/30/05 | 11:46 | 8015B/CA-LUFTE | . Yanna | 4925 |

Sample Extraction Data

| | Wt/Vol | | | | | |
|-----------|-----------|-------------|---------|------|----------|--------|
| Parameter | Extracted | Extract Vol | Date | Time | Analyst | Method |
| | | | | | | |
| трн-р | 1000 m | 1.00 ml | 3/28/05 | 9:15 | J. Davis | 3510 |



ANALYTICAL REPORT

Laboratory Number: 05-A41296 Sample ID: W-28-MW3

Page 2

| Surrogate | % Recovery | Target Range |
|---------------------------|------------|--------------|
| | | |
| TPH Hi Surr., o-Terphenyl | 91. | 55 133. |
| BTEX/GRO Surr., a,a,a-TFT | 94. | 69 132. |
| GC FID Surrogate | 60.0 | 50 150. |
| VOA Surr 1,2-DCA-d4 | 81. | 73 127. |
| VOA Surr Toluene-d8 | 100. | 79 113. |
| VOA Surr, 4-BFB | 96. | 79 125. |
| VOA Surr, DBFM | 100. | 75 134. |
| | | |

- ND = Not detected at the limit of Quantitation.
- U = Analyte analyzed for but not detected.
- # = Recovery outside Laboratory historical or method prescribed limits.
- J = All results evaluated to the Limit of Detection for reporting. Values below the Limit of Quantitation but above the Limit of Detection are qualified with J as estimated.
- ${\tt B}$ = Analyte was detected in the method blank.
- E = Estimated Value above the calibration limit of the instrument.



ANALYTICAL REPORT

ENVIRONMENTAL RESOLUTIONS, INC 10203

GEORGE SALLEY

20372 NORTH SEA CIRCLE LAKE FOREST, CA 92630

Project: ERI 3163 13

Project Name: EXXONMOBIL 18-MLJ

Sampler: JAMES CAVERS

Lab Number: 05-A41297 Sample ID: W-27-MW4

Sample Type: Water Site ID: 18-MLJ

Date Collected: 3/21/05

Time Collected: 14:35

Date Received: 3/23/05

Time Received: 7:50

Purchase Order: 4506125986

| tch |
|------|
| |
| |
| |
| 2734 |
| |
| 2734 |
| 4957 |
| 2734 |
| 2734 |
| 2734 |
| 2734 |
| 2734 |
| 2734 |
| 2734 |
| 2765 |
| |
| 4812 |
| 4925 |
| |

Sample Extraction Data

| | Wt/Vol | | | | | |
|-----------|-----------|-------------|---------|------|----------|--------|
| Parameter | Extracted | Extract Vol | Date | Time | Analyst | Method |
| | | | | | | |
| TPH-D | 1000 m | l 1.00 ml | 3/28/05 | 9:15 | J. Davis | 3510 |



ANALYTICAL REPORT

Laboratory Number: 05-A41297

Sample ID: W-27-MW4

Page 2

| Surrogate | % Recovery | Target Range |
|---------------------------|------------|--------------|
| | | |
| | | |
| TPH Hi Surr., o-Terphenyl | 83. | 55 133. |
| BTEX/GRO Surr., a,a,a-TFT | 104. | 69 132. |
| GC FID Surrogate | 65.0 | 50 150. |
| VOA Surr 1,2-DCA-d4 | 113. | 73 127. |
| VOA Surr Toluene-d8 | 111. | 79 113. |
| VOA Surr, 4-BFB | 110. | 79 125. |
| VOA Surr, DBFM | 110. | 75 134. |
| | | |

- ND = Not detected at the limit of Quantitation.
- U = Analyte analyzed for but not detected.
- # = Recovery outside Laboratory historical or method prescribed limits.
- ${\tt J}$ = All results evaluated to the Limit of Detection for reporting. Values below the Limit of Quantitation but above the Limit of Detection are qualified with ${\tt J}$ as estimated.
- B = Analyte was detected in the method blank.
- E = Estimated Value above the calibration limit of the instrument.



ANALYTICAL REPORT

ENVIRONMENTAL RESOLUTIONS, INC 10203

GEORGE SALLEY

20372 NORTH SEA CIRCLE LAKE FOREST, CA 92630

Project: ERI 3163 13

Project Name: EXXONMOBIL 18-MLJ

Sampler: JAMES CAVERS

Lab Number: 05-A41298 Sample ID: W-27-MW2 Sample Type: Water

Site ID: 18-MLJ

Date Collected: 3/21/05

Time Collected: 15:00
Date Received: 3/23/05

Time Received: 7:50

Purchase Order: 4506125986

| | | | | Limit of | Limit of | Dilution | | | | | |
|-----------|--------|------|-------|--------------|-----------|----------|------|------|--------|---------|-------|
| Parameter | Result | Flag | Units | Quantitation | Detection | Factor | Date | Time | Method | Analyst | Batch |
| | | | | | | | | | | | |
| | | | | | | | | | | | |

**Volatile Organics

| **Volatile Organics | | | | | | | | | | |
|--------------------------|--------|------|------|------|------|---------|-------|--------------|------------|------|
| **Ethyl-t-butylether | 0.60 J | ug/l | 1.00 | 0.27 | 1.0 | 3/25/05 | 16:25 | 8260B | S. Edwards | 2734 |
| **tert-amyl methyl ether | 0.70 J | ug/L | 1.00 | 0.30 | 1.0 | 3/25/05 | 16:25 | 8260B | S. Edwards | 2734 |
| **Tertiary butyl alcohol | 522. | ug/l | 100. | 42.8 | 10.0 | 3/27/05 | 2:17 | 8260B | I. Ahmed | 2742 |
| **Benzene | 80.7 | ug/l | 0.50 | 0.25 | 1.0 | 3/25/05 | 16:25 | 8260B | S. Edwards | 2734 |
| **Ethylbenzene | 538. | ug/l | 10.0 | 1.90 | 10.0 | 3/27/05 | 2:17 | 8260B | I. Ahmed | 2742 |
| **Toluene | 125. | ug/l | 0.50 | 0.17 | 1.0 | 3/25/05 | 16:25 | 8260B | S. Edwards | 2734 |
| **Xylenes (Total) | 90.1 | ug/l | 0.50 | 0.33 | 1.0 | 3/25/05 | 16:25 | 8260B | S. Edwards | 2734 |
| **Methyl-t-butyl ether | 1370 | ug/l | 20.0 | 2.30 | 10.0 | 3/27/05 | 2:17 | 8260B | I. Ahmed | 2742 |
| Ethanol | <200. | ug/L | 200. | 30.7 | 1. | 3/25/05 | 16:25 | 8260B | S. Edwards | 2734 |
| **Diisopropyl ether | <1.00 | ug/l | 1.00 | 0.18 | 1. | 3/25/05 | 16:25 | 8260/SA05-77 | S. Edwards | 2734 |
| **Methanol | <5000 | ug/l | 5000 | 160 | 1. | 3/30/05 | 14:14 | 8015B | K. Roberso | 2765 |
| | | | | | | | | | | |
| **TPH-GC | | | | | | | | | | |
| | | | | | | | | | | |

| **TPH | (Gasoline Range) | 2670 | ug/I | 500. | 330. | 10.0 | 3/31/05 | 11:36 | CA-LUFT | A. Cobbs | 7049 |
|-------|------------------------|-------|------|------|------|------|---------|-------|--------------|-----------|------|
| **TPH | (Diesel Range,C13-C22) | <500. | ug/l | 500. | 33. | 1. | 3/30/05 | 12:27 | 8015B/CA-LUF | TB. Yanna | 4925 |

Sample Extraction Data

| | Wt/Vol | | | | | |
|-----------|-----------|-------------|---------|------|----------|--------|
| Parameter | Extracted | Extract Vol | Date · | Time | Analyst | Method |
| | | | | | | |
| TPH-D | 1000 m | ıl 1.00 ml | 3/28/05 | 9:15 | J. Davis | 3510 |



2960 Foster Creighton Drive • Nashville, Tennessee 37204 800-765-0980 • 615-726-3404 Fax

ANALYTICAL REPORT

Laboratory Number: 05-A41298

Sample ID: W-27-MW2

Page 2

| Surrogate | % Recovery | Target Range |
|---------------------------|------------|--------------|
| | | |
| | | |
| TPH Hi Surr., o-Terphenyl | 74. | 55 133. |
| BTEX/GRO Surr., a,a,a-TFT | 94. | 69 132. |
| GC FID Surrogate | 63.0 | 50 150. |
| VOA Surr 1,2-DCA-d4 | 83. | 73 127. |
| VOA Surr Toluene-d8 | 100. | 79 113. |
| VOA Surr, 4-BFB | 100. | 79 125. |
| VOA Surr, DBFM | 102. | 75 134. |

- ND = Not detected at the limit of Quantitation.
- U = Analyte analyzed for but not detected.
- # = Recovery outside Laboratory historical or method prescribed limits.
- J = All results evaluated to the Limit of Detection for reporting. Values below the Limit of Quantitation but above the Limit of Detection are qualified with J as estimated.
- B = Analyte was detected in the method blank.
- ${\tt E}$ = Estimated Value above the calibration limit of the instrument.



2960 Foster Creighton Drive • Nashville, Tennessee 37204 800-765-0980 • 615-726-3404 Fax

ANALYTICAL REPORT

ENVIRONMENTAL RESOLUTIONS, INC 10203

GEORGE SALLEY

20372 NORTH SEA CIRCLE LAKE FOREST, CA 92630

Project: ERI 3163 13

Project Name: EXXONMOBIL 18-MLJ

Sampler: JAMES CAVERS

Lab Number: 05-A41299 Sample ID: W-27-MW5

Sample Type: Water Site ID: 18-MLJ

Date Collected: 3/21/05

Time Collected: 14:55

Date Received: 3/23/05 Time Received: 7:50

Purchase Order: 4506125986

| Parameter | Result | Flag | Units | Limit of Ouantitation | Limit of Detection | | Date | Time | Method | λns | alyst 1 | Batch |
|-------------------------------|--------|------|-------|--------------------------|--------------------|------|---------|-------|--------------|-----|---------|-------|
| | resuit | | | | | | | | | | | |
| **Volatile Organics | | | | | | | | | | | | |
| **Ethyl-t-butylether | <1.00 | | ug/l | 1.00 | 0.27 | 1. | 3/25/05 | 16:48 | 8260B | s. | Edwards | 2734 |
| **tert-amyl methyl ether | <1.00 | | ug/L | 1.00 | 0.30 | 1. | 3/25/05 | 16:48 | 8260B | s. | Edwards | 2734 |
| **Tertiary butyl alcohol | 5250 | | ug/l | 100. | 42.8 | 10.0 | 3/30/05 | 2:19 | 8260B | I. | Ahmed | 4957 |
| **Benzene | 23.1 | | ug/l | 0.50 | 0.25 | 1.0 | 3/25/05 | 16:48 | 8260B | s. | Edwards | 2734 |
| **Ethylbenzene | 8.10 | | ug/l | 0.50 | 0.19 | 1.0 | 3/25/05 | 16:48 | 8260B | s. | Edwards | 2734 |
| **Toluene | <0.50 | | ug/l | 0.50 | 0.17 | 1. | 3/25/05 | 16:48 | 8260B | s. | Edwards | 2734 |
| **Xylenes (Total) | 1.40 | | ug/l | 0.50 | 0.33 | 1.0 | 3/25/05 | 16:48 | 8260B | s. | Edwards | 2734 |
| **Methyl-t-butyl ether | 9.70 | | ug/l | 1.00 | 0.23 | 1.0 | 3/25/05 | 16:48 | 8260B | s. | Edwards | 2734 |
| Ethanol | <200. | | ug/L | 200. | 30.7 | 1. | 3/25/05 | 16:48 | 8260B | s. | Edwards | 2734 |
| **Diisopropyl ether | <1.00 | | ug/l | 1.00 | 0.18 | 1. | 3/25/05 | 16:48 | 8260/SA05-77 | s. | Edwards | 2734 |
| **Methanol | <5000 | | ug/l | 5000 | 160 | 1. | 3/30/05 | 14:20 | 8015B | ĸ. | Roberso | 2765 |
| **TPH-GC | | | | | | | | | | | | |
| **TPH (Gasoline Range) | 1420 | | ug/l | 50.0 | 33.0 | 1.0 | 3/29/05 | 23:09 | CA-LUFT | A. | Cobbs | 4812 |
| **TPH (Diesel Range, C13-C22) | 560. | | ug/l | 500. | 33. | 1.0 | 3/30/05 | 12:48 | 8015B/CA-LUF | TB. | Yanna | 4925 |

Sample Extraction Data

| | Wt/Vol | | | | | |
|-----------|-----------|-------------|---------|------|----------|--------|
| Parameter | Extracted | Extract Vol | Date | Time | Analyst | Method |
| | | | | | | |
| TPH-D | 1000 m | l 1.00 ml | 3/28/05 | 9:15 | J. Davis | 3510 |



ANALYTICAL REPORT

Laboratory Number: 05-A41299

Sample ID: W-27-MW5

Page 2

| Surrogate | % Recovery | Target Range |
|---------------------------|------------|--------------|
| | | |
| | | |
| TPH Hi Surr., o-Terphenyl | 74. | 55 133. |
| BTEX/GRO Surr., a,a,a-TFT | . 91. | 69 132. |
| GC FID Surrogate | 65.0 | 50 150. |
| VOA Surr 1,2-DCA-d4 | 106. | 73 127. |
| VOA Surr Toluene-d8 | 113. | 79 113. |
| VOA Surr, 4-BFB | 108. | 79 125. |
| VOA Surr, DBFM | 109. | 75 134. |

- ND = Not detected at the limit of Quantitation.
- U = Analyte analyzed for but not detected.
- # = Recovery outside Laboratory historical or method prescribed limits.
- ${\tt J}$ = All results evaluated to the Limit of Detection for reporting. Values below the Limit of Quantitation but above the Limit of Detection are qualified with ${\tt J}$ as estimated.
- B = Analyte was detected in the method blank.
- ${\tt E}$ = Estimated Value above the calibration limit of the instrument.



ANALYTICAL REPORT

ENVIRONMENTAL RESOLUTIONS, INC 10203

GEORGE SALLEY

20372 NORTH SEA CIRCLE LAKE FOREST, CA 92630

Project: ERI 3163 13

Project Name: EXXONMOBIL 18-MLJ

Sampler: JAMES CAVERS

Lab Number: 05-A41300 Sample ID: W-27-MW6

Sample Type: Water Site ID: 18-MLJ

Date Collected: 3/21/05

Time Collected: 15:10
Date Received: 3/23/05

Time Received: 7:50

Purchase Order: 4506125986

| Parameter | Result | Flag | Units | Limit of Quantitation | | Dilution Factor | Date | Time | Method | Analyst | Batch |
|------------------------------|--------|------|-------|--------------------------|------|--------------------|---------|-------|--------------|-----------|---------|
| **Volatile Organics | | | | | | | | | | | |
| **Ethyl-t-butylether | <1.00 | | ug/l | 1.00 | 0.27 | 1. | 3/25/05 | 17:10 | 8260B | S. Edward | ls 2734 |
| **tert-amyl methyl ether | <1.00 | | ug/L | 1.00 | 0.30 | 1. | 3/25/05 | 17:10 | 8260B | S. Edward | ls 2734 |
| **Tertiary butyl alcohol | <50.0 | | ug/l | 50.0 | 21.4 | 5. | 3/27/05 | 3:01 | 8260B | I. Ahmed | 2742 |
| **Benzene | <0.50 | | ug/l | 0.50 | 0.25 | 1. | 3/25/05 | 17:10 | 8260B | S. Edward | ls 2734 |
| **Ethylbenzene | 585. | | ug/l | 5.00 | 0.95 | 5.0 | 3/27/05 | 3:01 | 8260B | I. Ahmed | 2742 |
| **Toluene | <0.50 | | ug/l | 0.50 | 0.17 | 1. | 3/25/05 | 17:10 | 8260B | S. Edward | ls 2734 |
| **Xylenes (Total) | 122. | | ug/l | 0.50 | 0.33 | 1.0 | 3/25/05 | 17:10 | 8260B | S. Edward | ls 2734 |
| **Methyl-t-butyl ether | <1.00 | | ug/l | 1.00 | 0.23 | 1. | 3/25/05 | 17:10 | 8260B | S. Edward | ls 2734 |
| Ethanol | <200. | | ug/L | 200. | 30.7 | 1. | 3/25/05 | 17:10 | 8260B | S. Edward | ls 2734 |
| **Diisopropyl ether | <1.00 | | ug/l | 1.00 | 0.18 | 1. | 3/25/05 | 17:10 | 8260/SA05-77 | S. Edward | ls 2734 |
| **Methanol | 1200 | J | ug/l | 5000 | 160 | 1.0 | 3/31/05 | 14:06 | 8015B | K. Robers | 0 2766 |
| **TPH-GC | | | | | | | | | | | |
| **TPH (Gasoline Range) | 3960 | | ug/l | 500. | 330. | 10.0 | 3/31/05 | 12:11 | CA-LUFT | A. Cobbs | 7049 |
| **TPH (Diesel Range,C13-C22) | 749. | | ug/l | 500. | 33. | 1.0 | 3/30/05 | 13:09 | 8015B/CA-LUF | TB. Yanna | 4925 |
| | | | | | | | | | | | |

Sample Extraction Data

| | Wt/Vol | | | | | | |
|-----------|-----------|---------|-----|---------|------|----------|--------|
| Parameter | Extracted | Extract | Vol | Date | Time | Analyst | Method |
| | | | | | | | |
| יים אמיי | 1000 m | 1 1 00 | ml | 3/28/05 | 0.15 | .T Dawie | 3510 |



2960 Foster Creighton Drive • Nashville, Tennessee 37204 $800\text{-}765\text{-}0980 \bullet 615\text{-}726\text{-}3404 \text{ Fax}$

ANALYTICAL REPORT

Laboratory Number: 05-A41300

Sample ID: W-27-MW6

Page 2

| Surrogate | % Recovery | Target Range |
|---------------------------|------------|--------------|
| | | |
| • | | |
| TPH Hi Surr., o-Terphenyl | 70. | 55 133. |
| BTEX/GRO Surr., a,a,a-TFT | 100. | 69 132. |
| GC FID Surrogate | 73.0 | 50 150. |
| VOA Surr 1,2-DCA-d4 | 81. | 73 127. |
| VOA Surr Toluene-d8 | 98. | 79 113. |
| VOA Surr, 4-BFB | 99. | 79 125. |
| VOA Surr. DBFM | 104. | 75 134. |

- ND = Not detected at the limit of Quantitation.
- U = Analyte analyzed for but not detected.
- # = Recovery outside Laboratory historical or method prescribed limits.
- ${\tt J}$ = All results evaluated to the Limit of Detection for reporting. Values below the Limit of Quantitation but above the Limit of Detection are qualified with ${\tt J}$ as estimated.
- B = Analyte was detected in the method blank.
- E = Estimated Value above the calibration limit of the instrument.



ANALYTICAL REPORT

ENVIRONMENTAL RESOLUTIONS, INC 10203

GEORGE SALLEY

20372 NORTH SEA CIRCLE LAKE FOREST, CA 92630

Project: ERI 3163 13

Project Name: EXXONMOBIL 18-MLJ

Sampler: JAMES CAVERS

Lab Number: 05-A41301 Sample ID: TRIP BLANKS

Sample Type: Water Site ID: 18-MLJ

Date Collected: 3/21/05

Time Collected:

Date Received: 3/23/05

Time Received: 7:50

Purchase Order: 4506125986

| Parameter | Result | - | Limit of Quantitation | Limit of Detection | | Date | Time | Method | Analyst : | Batch |
|--------------------------|--------|--------------|-----------------------|-----------------------|------------|--------------|-------|--------------|------------|-------|
| | | | | | | | | | | |
| **Volatile Organics | | | | | | | | | | |
| **Ethyl-t-butylether | <1.00 | ug/I | 1.00 | 0.27 | 1. | 3/25/05 | 13:50 | 8260B | S. Edwards | 2734 |
| **tert-amyl methyl ether | <1.00 | ug/1 | 1.00 | 0.30 | 1. | 3/25/05 | 13:50 | 8260B | S. Edwards | 2734 |
| **Tertiary butyl alcohol | <10.0 | ug/ | 10.0 | 4.28 | 1. | 3/25/05 | 13:50 | 8260B | S. Edwards | 2734 |
| **Benzene | <0.50 | ug/ | L 0.50 | 0.25 | 1. | 3/25/05 | 13:50 | 8260B | S. Edwards | 2734 |
| **Ethylbenzene | <0.50 | ug/ | L 0.50 | 0.19 | 1. | 3/25/05 | 13:50 | 8260B | S. Edwards | 2734 |
| **Toluene | <0.50 | ug/ | 0.50 | 0.17 | 1. | 3/25/05 | 13:50 | 8260B | S. Edwards | 2734 |
| **Xylenes (Total) | <0.50 | ug/ | 0.50 | 0.33 | 1. | 3/25/05 | 13:50 | 8260B | S. Edwards | 2734 |
| **Methyl-t-butyl ether | <1.00 | ug/ | 1.00 | 0.23 | 1. | 3/25/05 | 13:50 | 8260B | S. Edwards | 2734 |
| **Diisopropyl ether | <1.00 | ug/ | 1.00 | 0.18 | 1. | 3/25/05 | 13:50 | 8260/SA05-77 | S. Edwards | 2734 |
| **TPH-GC | | | | | | | | | | |
| **TPH (Gasoline Range) | <50.0 | ug/] | 50.0 | 33.0 | 1. | 3/29/05 | 19:40 | CA-LUFT | A. Cobbs | 4812 |
| Guara sah a | | | 9. Danasa | Ma | P | | | | | |
| Surrogate | | | % Recovery | Та | arget Rang | je | | | | |

| Surrogate | % Recovery | Target Range | | |
|---------------------------|------------|--------------|--|--|
| | | | | |
| | | | | |
| BTEX/GRO Surr., a,a,a-TFT | 84. | 69 132. | | |
| VOA Surr 1,2-DCA-d4 | 81. | 73 127. | | |
| VOA Surr Toluene-d8 | 99. | 79 113. | | |
| VOA Surr, 4-BFB | 96. | 79 125. | | |
| VOA Surr DREM | 1.01 | 75 - 134 | | |



2960 Foster Creighton Drive • Nashville, Tennessee 37204 $800\text{-}765\text{-}0980 \, \bullet \, 615\text{-}726\text{-}3404 \,\, \text{Fax}$

ANALYTICAL REPORT

Laboratory Number: 05-A41301 Sample ID: TRIP BLANKS

sample in: Trip blank

Page 2

- ND = Not detected at the limit of Quantitation.
- U = Analyte analyzed for but not detected.
- # = Recovery outside Laboratory historical or method prescribed limits.
- J = All results evaluated to the Limit of Detection for reporting. Values below the Limit of Quantitation but above the Limit of Detection are qualified with J as estimated.
- B = Analyte was detected in the method blank.
- E = Estimated Value above the calibration limit of the instrument.



2960 Foster Creighton Drive • Nashville, Tennessee 37204 800-765-0980 • 615-726-3404 Fax

PROJECT QUALITY CONTROL DATA Project Number: ERI 3163 13

Page: 1

Matrix Spike Recovery

| Analyte | units | Orig. Val. | MS Val | Spike Conc | Recovery | Target Range | Q.C. Batch | Spike Sample |
|-----------------------------|-------------|-------------|--------|------------|----------|--------------|------------|--------------|
| | | | | | | | | |
| **UST ANALYSIS** | | | | • | | | | |
| TPH (Gasoline Range) | mg/l | < 0.0500 | 1.12 | 1.00 | 112 | 43 150. | 4812 | blank |
| TPH (Gasoline Range) | mg/l | < 0.0500 | 1.05 | 1.00 | 105 | 43 150. | 4812 | M:blank |
| TPH (Diesel Range, C13-C22) | mg/l | < 0.500 | 0.883 | 1.00 | 88 | 35 124. | 4925 | blank |
| TPH (Diesel Range, C13-C22) | mg/l | < 0.500 | 0.856 | 1.00 | 86 | 35 124. | 4925 | M:blank |
| BTEX/GRO Surr., a,a,a-TFT | % Recovery | | | | 113 | 69 132. | 4812 | |
| BTEX/GRO Surr., a,a,a-TFT | % Recovery | | | | 111 | 69 132. | 4812 | |
| | Matrix Spil | ke Recovery | | | | | | |
| Analyte | units | Orig. Val. | MS Val | Spike Conc | Recovery | Target Range | Q.C. Batch | Spike Sample |
| | | | | | | | | |
| **VOA PARAMETERS** | | | | | | | | |
| Benzene | mg/l | < 0.00025 | 0.0499 | 0.0500 | 100 | 62 143. | 2734 | BLANK |
| Benzene | mg/l | < 0.00025 | 0.0446 | 0.0500 | 89 | 62 143. | 2734 | M:BLANK |
| Toluene | mg/l | < 0.00017 | 0.0513 | 0.0500 | 103 | 63 141. | 2734 | BLANK |
| Toluene | mg/l | < 0.00017 | 0.0462 | 0.0500 | 92 | 63 141. | 2734 | M:BLANK |
| VOA Surr 1,2-DCA-d4 | % Rec | | | | 81 | 73 127. | 2734 | |
| VOA Surr 1,2-DCA-d4 | % Rec | | | | 77 | 73 127. | 2734 | |
| VOA Surr 1,2-DCA-d4 | % Rec | | | | 81 | 73 127. | 2742 | |
| VOA Surr 1,2-DCA-d4 | % Rec | | | | 80 | 73 127. | 2742 | |
| VOA Surr Toluene-d8 | % Rec | | | | 100 | 79 113. | 2734 | |
| VOA Surr Toluene-d8 | % Rec | | | | 101 | 79 113. | 2734 | |
| VOA Surr Toluene-d8 | % Rec | | | | 95 | 79 113. | 2742 | |
| VOA Surr Toluene-d8 | % Rec | | | | 97 | 79 113. | 2742 | |
| VOA Surr, 4-BFB | % Rec | | | | 96 | 79 125. | 2734 | |
| VOA Surr, 4-BFB | % Rec | | | | 94 | 79 125. | 2734 | |
| VOA Surr, 4-BFB | % Rec | | | | 98 | 79 125. | 2742 | |
| VOA Surr, 4-BFB | % Rec | | | | 101 | 79 125. | 2742 | |
| VOA Surr, DBFM | % Rec | | | | 98 | 75 134. | 2734 | |
| VOA Surr, DBFM | % Rec | | | | 101 | 75 134. | 2734 | |
| VOA Surr, DBFM | % Rec | | | | 102 | 75 134. | 2742 | |



2960 Foster Creighton Drive • Nashville, Tennessee 37204 800-765-0980 • 615-726-3404 Fax

PROJECT QUALITY CONTROL DATA Project Number: ERI 3163 13

Page: 2

Matrix Spike Recovery

| Analyte | units | Orig. Val. | MS Val | Spike Conc | Recovery | Target Range | Q.C. Batch | Spike Sample |
|-----------------------------|--------------|------------|-----------|------------|----------|--------------|------------|--------------|
| | | | | | | | | |
| VOA Surr, DBFM | % Rec | | | | 97 | 75 134. | 2742 | |
| | Matrix Spik | e Recovery | | | | | | , |
| Analyte | units | Orig. Val. | MS Val | Spike Conc | Recovery | Target Range | Q.C. Batch | Spike Sample |
| | | | | | | | | |
| **MISC PARAMETERS** | | | | | | | | |
| Methanol | mg/l | 1.40 | 43.2 | 50.0 | 84 | 40 - 140 | 2765 | 05-A41198 |
| Methanol | mg/l | 1.40 | 46.9 | 50.0 | 91 | 40 - 140 | 2765 | M:05A41198 |
| Methanol | mg/l | 1.20 | 46.8 | 50.0 | 91 | 40 - 140 | 2766 | 05-A41300 |
| Methanol | mg/l | 1.20 | 50.1 | 50.0 | 98 | 40 - 140 | 2766 | M:05A41300 |
| | Matrix Spike | Duplicate | | | | | | |
| Analyte | units | Orig. Val. | Duplicate | RPD | Limit | Q.C. Batch | | |
| **UST PARAMETERS** | | | | | | | | |
| TPH (Gasoline Range) | mg/l | 1.12 | 1.05 | 6.45 | 27. | 4812 | | |
| TPH (Diesel Range, C13-C22) | mg/l | 0.883 | 0.856 | 3.11 | 36. | 4925 | | |
| BTEX/GRO Surr., a,a,a-TFT | % Recovery | | 111. | | | 4812 | | |
| | Matrix Spike | Duplicate | | | | | | |
| Analyte | units | Orig. Val. | Duplicate | RPD | Limit | Q.C. Batch | | |
| | | | | | | | | |
| **VOA PARAMETERS** | | | | | • | | | |
| Benzene | mg/l | 0.0499 | 0.0446 | 11.22 | 27. | 2734 | | |
| Toluene | | | | | | | | |



PROJECT QUALITY CONTROL DATA Project Number: ERI 3163 13

Page: 3

| VOA Surr 1,2-DCA-d4 | % Rec | 77. | 2734 |
|---------------------|-------|------|------|
| VOA Surr 1,2-DCA-d4 | % Rec | 80. | 2742 |
| VOA Surr Toluene-d8 | % Rec | 101. | 2734 |
| VOA Surr Toluene-d8 | % Rec | 97. | 2742 |
| VOA Surr, 4-BFB | % Rec | 94. | 2734 |
| VOA Surr, 4-BFB | % Rec | 101. | 2742 |
| VOA Surr, DBFM | % Rec | 101. | 2734 |
| VOA Surr, DBFM | % Rec | 97. | 2742 |

Matrix Spike Duplicate

| Analyte | units | Orig. Val. | Duplicate | RPD | Limit | Q.C. Batch |
|---------------------|-------|------------|-----------|------|-------|------------|
| | | | | | | |
| | | | | | | |
| **MISC PARAMETERS** | | | | | | |
| Methanol | mg/l | 43.2 | 46.9 | 8.21 | 50 | 2765 |
| Methanol | mg/l | 46.8 | 50.1 | 6.81 | 50 | 2766 |

Laboratory Control Data

| Analyte | units | Known Val. | Analyzed Val | % Recovery | Target Range | Q.C. Batch |
|-----------------------------|------------|------------|--------------|------------|--------------|------------|
| | | | | | | |
| | | | | | | |
| **UST PARAMETERS** | | | | | | |
| TPH (Gasoline Range) | mg/l | 1.00 | 1.09 | 109 | 64 - 130 | 4812 |
| TPH (Gasoline Range) | mg/l | 1.00 | 1.11 | 111 | 64 - 130 | 7049 |
| TPH (Diesel Range, C13-C22) | mg/l | 1.00 | 1.11 | 111 | 41 - 120 | 4925 |
| BTEX/GRO Surr., a,a,a-TFT | % Recovery | | | 110 | 69 - 132 | 4812 |
| BTEX/GRO Surr., a,a,a-TFT | % Recovery | | | 106 | 69 - 132 | 7049 |

Laboratory Control Data

| Analyte | units | Known Val. | Analyzed Val | % Recovery | Target Range | Q.C. Batch |
|------------------------|-------|------------|--------------|------------|--------------|------------|
| | | | | | | |
| | | | | | | |
| **VOA PARAMETERS** | | | | | | |
| Ethyl-t-butylether | mg/l | 0.0500 | 0.0392 | 78 | 67 - 140 | 2734 |
| tert-amyl methyl ether | mg/L | 0.0500 | 0.0431 | 86 | 68 - 134 | 2734 |
| Tertiary butyl alcohol | mg/l | 0.500 | 0.435 | 87 | 28 - 182 | 2734 |



PROJECT QUALITY CONTROL DATA Project Number: ERI 3163 13 Page: 4

Laboratory Control Data

| Analyte | units | Known Val | Analyzed Val | % Recovery | Target Range | O C Batch |
|------------------------|-------|-----------|--------------|------------|--------------|-----------|
| | | | | | | |
| Tertiary butyl alcohol | mg/l | 0.500 | 0.485 | 97 | 28 - 182 | 2742 |
| Tertiary butyl alcohol | mg/l | 0.500 | 0.570 | 114 | 28 - 182 | 4957 |
| Benzene | mg/l | 0.0500 | 0.0482 | 96 | 78 - 123 | 2734 |
| Ethylbenzene | mg/l | 0.0500 | 0.0467 | 93 | 80 - 124 | 2734 |
| Ethylbenzene | mg/l | 0.0500 | 0.0433 | 87 | 80 - 124 | 2742 |
| Toluene | mg/l | 0.0500 | 0.0524 | 105 | 77 - 124 | 2734 |
| Xylenes (Total) | mg/l | 0.150 | 0.146 | 97 | 81 - 124 | 2734 |
| Methyl-t-butyl ether | mg/l | 0.0500 | 0.0415 | 83 | 69 - 136 | 2734 |
| Methyl-t-butyl ether | mg/l | 0.0500 | 0.0427 | 85 | 69 - 136 | 2742 |
| Ethanol | mg/L | 5.00 | 5.00 | 100 | 48 - 164 | 2734 |
| Diisopropyl ether | mg/l | 0.0500 | 0.0467 | 93 | 65 - 140 | 2734 |
| Methanol | mg/l | 50.0 | 44.8 | 90 | 69 - 125 | 2765 |
| Methanol | mg/l | 50.0 | 48.9 | 98 | 69 - 125 | 2766 |
| VOA Surr 1,2-DCA-d4 | % Rec | | | 79 | 73 - 127 | 2734 |
| VOA Surr 1,2-DCA-d4 | % Rec | | | 86 | 73 - 127 | 2742 |
| VOA Surr 1,2-DCA-d4 | % Rec | | | 113 | 73 - 127 | 4957 |
| VOA Surr Toluene-d8 | % Rec | | | 101 | 79 - 113 | 2734 |
| VOA Surr Toluene-d8 | % Rec | | | 98 | 79 - 113 | 2742 |
| VOA Surr Toluene-d8 | % Rec | | | 108 | 79 - 113 | 4957 |
| VOA Surr, 4-BFB | % Rec | | | 95 | 79 - 125 | 2734 |
| VOA Surr, 4-BFB | % Rec | | | 102 | 79 - 125 | 2742 |
| VOA Surr, 4-BFB | % Rec | | | 106 | 79 - 125 | 4957 |
| VOA Surr, DBFM | % Rec | | | 97 | 75 - 134 | 2734 |
| VOA Surr, DBFM | % Rec | | | 102 | 75 - 134 | 2742 |
| VOA Surr, DBFM | % Rec | | | 110 | 75 - 134 | 4957 |

Laboratory Control Data

| Analyte | units | Known Val. | Analyzed Val | % Recovery | Target Range | Q.C. Batch |
|---------------------|-------|------------|--------------|------------|--------------|------------|
| | | | | | | |
| | | | | | | |
| **MISC PARAMETERS** | | | | | | |
| Methanol | mg/l | 50.0 | 44.8 | 90 | 69 - 125 | 2765 |
| Methanol | mg/l | 50.0 | 48.9 | 98 | 69 - 125 | 2766 |



2960 Foster Creighton Drive • Nashville, Tennessee 37204 800-765-0980 • 615-726-3404 Fax

PROJECT QUALITY CONTROL DATA Project Number: ERI 3163 13

Page: 5

Blank Data

| Analyte | Blank Value | Units | Q.C. Batch | Date Analyzed | Time Analyzed |
|--|---|--|--|--|--|
| | | | | | |
| | | | | | |
| **UST PARAMETERS** | • | | | | |
| TPH (Gasoline Range) | < 0.0500 | mg/l | 4812 | 3/29/05 | 11:26 |
| TPH (Gasoline Range) | < 0.0500 | mg/l | 7049 | 3/31/05 | 11:01 |
| TPH (Diesel Range, C13-C22) | < 0.500 | mg/l | 4925 | 3/30/05 | 9:02 |
| | Blank Data | | | | |
| | | | | | |
| Analyte | Blank Value | Units | Q.C. Batch | Date Analyzed | Time Analyzed |
| | | | | | |
| **UST PARAMETERS** | | | | | |
| BTEX/GRO Surr., a,a,a-TFT | 83. | % Recovery | 4812 | 3/29/05 | 11:26 |
| BTEX/GRO Surr., a,a,a-TFT | 91. | % Recovery | | 3/31/05 | 11:01 |
| 2, | 52. | | ,015 | 3,31,03 | 11.01 |
| | Blank Data | | | | |
| | | | | | |
| | | | | | |
| Analyte | Blank Value | | | Date Analyzed | - |
| | Blank Value | Units | Q.C. Batch | Date Analyzed | Time Analyzed |
| - | Blank Value | | | - | = |
| | Blank Value | | | - | = |
| **VOA PARAMETERS** | | mg/l | | | |
| **VOA PARAMETERS** Ethyl-t-butylether | < 0.00027 | mg/l mg/L | 2734 | 3/25/05 | 13:27 |
| **VOA PARAMETERS** Ethyl-t-butylether tert-amyl methyl ether | < 0.00027 < 0.00030 | mg/l mg/L mg/l | 2734 2734 | 3/25/05 3/25/05 | 13:27 |
| **VOA PARAMETERS** Ethyl-t-butylether tert-amyl methyl ether Tertiary butyl alcohol | < 0.00027 < 0.00030 < 0.00428 | mg/l mg/L mg/l mg/l | 2734 2734 2734 | 3/25/05 3/25/05 3/25/05 | 13:27 13:27 13:27 |
| **VOA PARAMETERS** Ethyl-t-butylether tert-amyl methyl ether Tertiary butyl alcohol Tertiary butyl alcohol | < 0.00027 < 0.00030 < 0.00428 < 0.00428 | mg/l mg/L mg/l mg/l mg/l | 2734 2734 2734 2734 | 3/25/05 3/25/05 3/25/05 3/26/05 | 13:27 13:27 13:27 18:09 |
| **VOA PARAMETERS** Ethyl-t-butylether tert-amyl methyl ether Tertiary butyl alcohol Tertiary butyl alcohol Tertiary butyl alcohol | < 0.00027 < 0.00030 < 0.00428 < 0.00428 | mg/l mg/L mg/l mg/l mg/l | 2734 2734 2734 2742 4957 | 3/25/05 3/25/05 3/25/05 3/26/05 3/29/05 | 13:27 13:27 13:27 18:09 20:01 |
| **VOA PARAMETERS** Ethyl-t-butylether tert-amyl methyl ether Tertiary butyl alcohol Tertiary butyl alcohol Tertiary butyl alcohol Benzene | < 0.00027 < 0.00030 < 0.00428 < 0.00428 < 0.00025 | mg/l mg/L mg/l mg/l mg/l mg/l | 2734 2734 2734 2742 4957 2734 | 3/25/05 3/25/05 3/25/05 3/26/05 3/29/05 3/25/05 | 13:27 13:27 13:27 18:09 20:01 |
| **VOA PARAMETERS** Ethyl-t-butylether tert-amyl methyl ether Tertiary butyl alcohol Tertiary butyl alcohol Tertiary butyl alcohol Benzene Ethylbenzene | < 0.00027 < 0.00030 < 0.00428 < 0.00428 < 0.00425 < 0.00019 | mg/l mg/L mg/l mg/l mg/l mg/l mg/l mg/l | 2734 2734 2734 2742 4957 2734 | 3/25/05 3/25/05 3/25/05 3/26/05 3/29/05 3/25/05 3/25/05 | 13:27 13:27 13:27 18:09 20:01 13:27 |
| **VOA PARAMETERS** Ethyl-t-butylether tert-amyl methyl ether Tertiary butyl alcohol Tertiary butyl alcohol Tertiary butyl alcohol Benzene Ethylbenzene Ethylbenzene | < 0.00027 < 0.00030 < 0.00428 < 0.00428 < 0.00428 < 0.00025 < 0.00019 | mg/l mg/l mg/l mg/l mg/l mg/l mg/l mg/l | 2734 2734 2734 2742 4957 2734 2734 | 3/25/05 3/25/05 3/25/05 3/26/05 3/29/05 3/25/05 3/25/05 | 13:27 13:27 13:27 18:09 20:01 13:27 13:27 18:09 |
| **VOA PARAMETERS** Ethyl-t-butylether tert-amyl methyl ether Tertiary butyl alcohol Tertiary butyl alcohol Tertiary butyl alcohol Benzene Ethylbenzene Ethylbenzene Toluene | < 0.00027 < 0.00030 < 0.00428 < 0.00428 < 0.00025 < 0.00019 < 0.00019 | mg/l mg/l mg/l mg/l mg/l mg/l mg/l mg/l | 2734 2734 2734 2742 4957 2734 2734 2742 | 3/25/05 3/25/05 3/25/05 3/26/05 3/29/05 3/25/05 3/25/05 3/26/05 | 13:27 13:27 13:27 18:09 20:01 13:27 13:27 18:09 |
| **VOA PARAMETERS** Ethyl-t-butylether tert-amyl methyl ether Tertiary butyl alcohol Tertiary butyl alcohol Tertiary butyl alcohol Benzene Ethylbenzene Ethylbenzene Toluene Xylenes (Total) | < 0.00027 < 0.00030 < 0.00428 < 0.00428 < 0.00025 < 0.00019 < 0.00017 < 0.0003 | mg/l mg/l mg/l mg/l mg/l mg/l mg/l mg/l | 2734 2734 2734 2742 4957 2734 2734 2742 2734 | 3/25/05 3/25/05 3/25/05 3/26/05 3/29/05 3/25/05 3/25/05 3/25/05 3/25/05 | 13:27 13:27 13:27 18:09 20:01 13:27 13:27 18:09 13:27 |
| **VOA PARAMETERS** Ethyl-t-butylether tert-amyl methyl ether Tertiary butyl alcohol Tertiary butyl alcohol Benzene Ethylbenzene Ethylbenzene Toluene Xylenes (Total) Methyl-t-butyl ether | < 0.00027 < 0.00030 < 0.00428 < 0.00428 < 0.00025 < 0.00019 < 0.00017 < 0.00033 < 0.00023 | mg/l mg/l mg/l mg/l mg/l mg/l mg/l mg/l | 2734 2734 2734 2742 4957 2734 2734 2742 2734 2734 2734 | 3/25/05 3/25/05 3/25/05 3/26/05 3/29/05 3/25/05 3/25/05 3/25/05 3/25/05 3/25/05 | 13:27 13:27 13:27 18:09 20:01 13:27 13:27 18:09 13:27 13:27 |



PROJECT QUALITY CONTROL DATA Project Number: ERI 3163 13

Page: 6

| VOA Surr 1,2-DCA-d4 | 82. | % Rec | 2734 | 3/25/05 | 13:27 |
|---------------------|------|-------|------|---------|-------|
| VOA Surr 1,2-DCA-d4 | 81. | % Rec | 2742 | 3/26/05 | 18:09 |
| VOA Surr 1,2-DCA-d4 | 107. | % Rec | 4957 | 3/29/05 | 20:01 |
| VOA Surr Toluene-d8 | 100. | % Rec | 2734 | 3/25/05 | 13:27 |
| VOA Surr Toluene-d8 | 96. | % Rec | 2742 | 3/26/05 | 18:09 |
| VOA Surr Toluene-d8 | 112. | % Rec | 4957 | 3/29/05 | 20:01 |
| VOA Surr, 4-BFB | 99. | % Rec | 2734 | 3/25/05 | 13:27 |
| VOA Surr, 4-BFB | 103. | % Rec | 2742 | 3/26/05 | 18:09 |
| VOA Surr, 4-BFB | 110. | % Rec | 4957 | 3/29/05 | 20:01 |
| VOA Surr, DBFM | 101. | % Rec | 2734 | 3/25/05 | 13:27 |
| VOA Surr, DBFM | 103. | % Rec | 2742 | 3/26/05 | 18:09 |
| VOA Surr, DBFM | 105. | % Rec | 4957 | 3/29/05 | 20:01 |

Blank Data

| Blank Value | Units | Q.C. Batch | Date Analyzed | Time Analyzed |
|-------------|-------|------------|----------------|------------------------|
| | | | | |
| • | | | | |
| | | | | |
| 4.40 | mg/l | 2765 | 3/30/05 | 12:02 |
| < 0.16 | mg/l | 2766 | 3/31/05 | 13:10 |
| | 4.40 | 4.40 mg/l | 4.40 mg/l 2765 | 4.40 mg/l 2765 3/30/05 |

^{# =} Value outside Laboratory historical or method prescribed QC limits.

End of Report for Project 410354



Nashville Division

COOLER RECEIPT FORM

BC#



Client Name :_ERI Cooler Received/Opened On: 3/23/05 Accessioned By: James D. Jacobs Log-in Personnel Signature 1. Temperature of Cooler when triaged: 0,5 **Degrees Celsius** Were custody seals on outside of cooler?.... a. If yes, how many and where:_____ / Front 3. Were custody seals on containers?...../NQ...YES...NA Were custody papers inside cooler?.... KES....NO...NA Were custody papers properly filled out (ink, signed, etc)?.... YES...NO...NA 7. Did you sign the custody papers in the appropriate place?..... NES)...NO...NA 8. What kind of packing material used? Bubblewrap Peanuts Vermiculite Other None Cooling process: Ice-pack Ice (direct contact) Dry ice Other None 10. Did all containers arrive in good condition (unbroken)?..... /YE\$...NO...NA 11. Were all container labels complete (#, date, signed, pres., etc)?..... YES...NO...NA 13. Were correct containers used for the analysis requested?...... YES)..NO...NA ..NO...NA 16. Were correct preservatives used? If not, record standard ID of preservative used here 17. Was residual chlorine present? NO...YES. 18. Indicate the Airbill Tracking Number (last 4 digits for Fedex only) and Name of Courier below: <u>9854</u> Fed-Ex UPS DHL Velocity Route Off-street Misc. 19. If a Non-Conformance exists, see attached or comments below:

Test/America

Nashville Division 2960 Foster Creighton Nashville, TN 37204 Phone: 615-726-0177-Toll Free: 800-765-0980 Fax: 615-726-3404 410354

ExonMobil

10203 PG. OF |

| Consultant Name: | Enviro | nmental | Res | oluti | ons, l | nc. | • | | | | | | | | | | | T | A Accou | int #: _ | | | | | | 1 | 020 |)3 | | | | | |
|--|--------------|--------------|---------------------------|----------|-----------|----------------|----------|------------------|---------------------------------------|------------------------------|---------------------------|------------------------------|---------------------|------------|----------------|-------------|-----------|------------------|---------------------------|------------------|--|--------------------|----------------|------------------------------------|-------------------|--|-----------------|-----------------|--------------------|--|-------------------|-------------------------|-------------------------------------|
| Address: | 20372 | North S | ea C | Cirlole | 9 | | | | | | | | | | | | | | Invoice | e To: | | | | | Ма | rla | Gu | <u>ien</u> | sler | <u>. </u> | | | |
| City/State/Zip: | Lake F | orest, C | A 9 | 2630 | 0 | | | | | | | | | | | | | | Repor | t To: | | | | <u> </u> | GE | OR | GE | SA | LLY | _ | | | |
| ExxonMobil Territory Mgr: | Maria | Guens | ler | | | | | | | | | | | | | | | | F | PO#: | | | | | | ; | 200 | 5_ | | | | | |
| Consultant Project Mgr: | GEOR | GE SAI | LLY | | | | | | | | | | | | | | | | Facility | ID# | | | ERI | 3163 | 13 | / E | XXC | INC | MOE | 3IL | 181 | ИL. | <u> </u> |
| Consultant Telephone Number: | 949-45 | 7-8950 | | | | Fa | x No |).; <u>{</u> | 49 | 457 | 7-8 | 956 | | | | | | 8 | Site Add | ress | | | 50 | 05 NO | DRI | ГΗ | LOI | √G | BE/ | <u>AC</u> ł | Н, С | <u> </u> | |
| Sampler Name: (Print) | JAM | 66 D | _ (| MANE | 516 | | | _ | | | | | | | | | | Cit | ty, State | , ZIp | | | | L | .00 | IG I | BEA | /CH | 1, C | <u>A</u> | | | |
| Sampler Signature: | | | 1 | | | | | | | | | | | | Re | egul | lato | ry | District | (CA) | | | | | | LAF | ?W | QC | 8 | | | | - · · · · · · · · · · · · · · · · · |
| | | | | | | | Г | F | res | erval | live | | T | | Ма | trix | | T | | | | An | alyze | For: | | | | | | 1 | | | |
| cueverty on . | Date Sampled | Time Sampled | No. of Containers Shipped | Grab | Composite | Field Filtered | Methanol | Sodium Bisuifate | Hol (Blue Label) NaOH (Orange Label) | H₂SO₄ Plastic (Yellow Label) | 1,904 Glass(Yellow Label) | INO ₃ (Red Label) | Norte (Black Label) | Vastewater | Drinking Water | Sludge | Soil | Ather (specify): | 8015M DIESEL- CAL LUFT | TPH/GAS-CAL LUFT | FULL SCAN 8260B +OXYGENATES / GC/MS | METHANOL -CAL LUFT | ETHANOL (8260) | *8260B/BTEX +OXYGENATES / GC/MS | STEX/MTBE BY 8021 | 8010 | REDOX POTENTIAL | NITRATE/SULFATE | METHANE(8015) | RUSH TAT (Pre-Schedule) | 5 Day TAT request | Fax Results (yes or no) | Due Date of Report |
| Sample ID or Field ID W- 79- MW | | <u> </u> | | | - | <u> </u> | 2 | | + | 1 | + | | - | | | 8 | 9 | 4 | | | <u> </u> | | $\overline{}$ | | - | o | | ~- | ≥ | 严 | 1 | ٣ | |
| (W-29-MW) | 3.21.00 | | 6 | X | ļ | | H | - - | X | - | | | 4 | 4 | \sqcup | \vdash | \dashv | - | X | Х | | 1 | X | X | ┼- | 14 | _ | 94 | + | \vdash | X | \dashv | |
| W-29-MW1 | 1- | 1430 | | - | ļ | | | 4 | Н- | 1 | Н | - | 4 | ╟ | | \sqcup | 4 | 4 | N | Λ | | 1 | | χ, | ╀ | # | 29 | - | ╀- | \bot | H | \dashv | |
| W-29-MW1 W-28-MW3 W-27-MW4 | | 1450 | | - | ļ | <u> </u> | Ц | \perp | Щ. | | | | 4 | Щ. | Н | | 4 | _ | 1 | 71 | | 1 | | × | igspace | $\!$ | 29 | 1- | \bot | \perp | \coprod | Ц | |
| W-27 - MW4 | | 1435 | | | _ | | | \perp | | $oldsymbol{\perp}$ | | | 4 | Щ | Ш | | \perp | _ | 7 | 7 | | 1 | 1 | 20 | | \coprod | + + | 72 | \perp | $oldsymbol{\perp}$ | Ш | Ц | |
| W-27-MW2 | | 1500 | | | <u> </u> | | Ц | Ш | | | Ц | | | | Ц | | \perp | | 7 | 71 | | N | _ | N | | \coprod | | 18 | $oldsymbol{\perp}$ | L | Ш | | |
| (W-27- MW5 | | 1455 | | | <u> </u> | | | | | | | | | | | | \perp | | 2 | 7 | | 1 | K | 7 | | \coprod | 29 | 9 | \perp | L | Ш | Ц | |
| 111-27-MW6 | | 1510 | \checkmark | | | | | | | | | | | | | | | | × | P | | X | X | Ø | | | 30 | 0 | \perp | L | Ш | Ш | |
| TIMP BLANCE | V | / | 4 | V | | | | 1 | 1 | | | | N | Y | | | | | | Ø | | | | K | L | 4 | 130 | 1 | L | L | A | | |
| | | | | | | | | | | | | | | | | | | Ī | | | | | | | | | | | | L | | | |
| | | | | | | | | | T | | | П | T | | | П | | | | | | Γ | П | | Τ | Ţ | T | T | T | Τ | | | |
| Comments/Special Instructions: | | SENAT | | | | QUI | EST | ΈD | AE | ov | E | | | | | | | | | | Labo | Te | mpe | ature | Upo | n Re | | | 1 | | ے ج م | | |
| CONSULTANT ID # ERIL | | | | | | | | | | | | 'P | LEA | SE | | | | | DF FILE | | | | - | Conta | | | | | | 8 |) | N N | |
| GLOBAL ID # T0603701794 Relinquished by: | D | ate | Ti | me | Rece | lved b | oy: | | | | | 1 | · | V | | ate | . <u></u> | (W | Time | | QC D | | | | | - | - | | | w. | | 14 | |
| Jan 1/2 | 3/2 | 2/05 | | 10 | _ | | _ | | | | | | | 15 | | 22/c ate | 4 | // | //o | | Level Level Level | 3 | | 5 DA | | | | | | | | | |
| Relinfulshed by: | 3/2 | ate 2/05 | /sa | me 10 | Rece | :iveQ (| uy (L | an b | erso | | b | سرا | 7 | | 3/2 | | źs | | 75° | | Site S Projec | peci | | yes, pl | ease | | | pro | e-scl | hedu | | | stAmerica |

| CLIENT NA | ME: EXXON | MOBIL 18M | <u>LJ</u> | ERI JOE | 3 # 3163 13 | | 0.163 FO | R A 2" W | ELL |
|---------------------------|--|---|--------------------------|-------------------------|---------------------|---|--|---|--|
| SITE LOCA | TION: 5005 | N. LONG BEA | ACH BLVD | ANALY | SIS: TPHg/8 | 8260B | 0.652 FO | R A 4" W | /ELL |
| FIELD CRE | W:JC/EG | DATE: 3/21/ | 05 | TPHd | | | | R A 6" W | |
| | | | ДЕРТН ТО | | CASE | PRG | 1.107 FO | 1 1 | |
| WELL# | TIME | WATER | WELL | DIA | VOL(gal) | VOL | COND. | TEMP | pН |
| MW7 | 12:55 PM | 29.09 | 48.35 | 4 | 12.57 | 39 | 1 00.121 | 12.112 | PII |
| | 1:08 PM | | | | | 1 | 3.03 | 71.4 | 8.14 |
| | 1:14 PM | | | - | | 13 | 3.01 | 71.0 | 8.09 |
| | 1:20 PM | | | | | 26 | 2.97 | 70.2 | 8.03 |
| | 1:26 PM | | | | | 39 | 2.94 | 70.5 | 8.01 |
| SW | 2:40 PM | 29.88 | | | | | | | |
| | | DEPTH TO | ДЕРТН ТО | CASE | CASE | PRG | T | : | |
| WELL# | TIME | WATER | WELL | DIA | VOL | VOL | COND. | TEMP | Hq |
| MW1 | 12:57 PM | 29.21 | 49.61 | 4 | 13.32 | 39 | | | |
| | | | | | | | | 70.4 | 7.41 |
| | 1:08 PM | | 1 | | [] | 1 | 2.16 | 73.1 | 1.4 |
| | 1:08 PM 1:14 PM | | | · | | 13 | 2.16 2.11 | 73.1 72.7 | 7.36 |
| | | | | | | | | | 7.36 |
| | 1:14 PM | | | | | 13 | 2.11 | 72.7 | 7.36 7.38 |
| SW COMMENTS | 1:14 PM 1:21 PM 1:28 PM 2:30 PM | 30,33 | | | | 13 26 | 2.11 2.06 | 72.7 72.4 | |
| COMMENTS | 1:14 PM 1:21 PM 1:28 PM 2:30 PM S Water Clea | ДЕРТН ТО | ДЕРТН ТО | CASE | CASE | 13 26 39 PRG | 2.11 2.06 2.05 | 72.7 72.4 72.2 | 7.36 7.38 7.39 |
| COMMENTS | 1:14 PM 1:21 PM 1:28 PM 2:30 PM S Water Clear | DEPTH TO WATER | WELL | DIA | VOL | 13 26 39 PRG VOL | 2.11 2.06 | 72.7 72.4 | 7.36 7.38 |
| COMMENTS | 1:14 PM 1:21 PM 1:28 PM 2:30 PM S Water Clean TIME 12:59 PM | ДЕРТН ТО | | | | 13 26 39 PRG VOL 36 | 2.11 2.06 2.05 | 72.7 72.4 72.2 TEMP | 7.36 7.38 7.39 |
| COMMENTS | 1:14 PM 1:21 PM 1:28 PM 2:30 PM 5 Water Clean TIME 12:59 PM 1:08 PM | DEPTH TO WATER | WELL | DIA | VOL | 13 26 39 PRG VOL 36 1 | 2.11 2.06 2.05 COND. | 72.7 72.4 72.2 TEMP | 7.36 7.38 7.39 pH |
| COMMENTS WELL# | 1:14 PM 1:21 PM 1:28 PM 2:30 PM 5 Water Clean TIME 12:59 PM 1:08 PM 1:13 PM | DEPTH TO WATER | WELL | DIA | VOL | 13 26 39 PRG VOL 36 1 | 2.11 2.06 2.05 COND. | 72.7 72.4 72.2 TEMP 72.2 71.9 | 7.36 7.38 7.39 pH 7.77 7.76 |
| COMMENTS WELL# | 1:14 PM 1:21 PM 1:28 PM 2:30 PM 5 Water Clean TIME 12:59 PM 1:08 PM 1:13 PM 1:19 PM | DEPTH TO WATER | WELL | DIA | VOL | 13 26 39 PRG VOL 36 1 12 24 | 2.11 2.06 2.05 COND. 2.87 2.82 2.77 | 72.7 72.4 72.2 TEMP 72.2 71.9 71.6 | 7.36 7.38 7.39 pH 7.77 7.76 |
| WELL# | 1:14 PM 1:21 PM 1:28 PM 2:30 PM 8 Water Clear TIME 12:59 PM 1:08 PM 1:13 PM 1:19 PM 1:25 PM | DEPTH TO WATER 28.88 | WELL | DIA | VOL | 13 26 39 PRG VOL 36 1 | 2.11 2.06 2.05 COND. | 72.7 72.4 72.2 TEMP 72.2 71.9 | 7.36 7.38 7.39 pH 7.77 7.76 7.72 |
| WELL # MW3 | 1:14 PM 1:21 PM 1:28 PM 2:30 PM 8 Water Clear TIME 12:59 PM 1:08 PM 1:13 PM 1:19 PM 1:25 PM 2:50 PM | DEPTH TO WATER 28.88 | WELL | DIA | VOL | 13 26 39 PRG VOL 36 1 12 24 | 2.11 2.06 2.05 COND. 2.87 2.82 2.77 | 72.7 72.4 72.2 TEMP 72.2 71.9 71.6 | 7.36 7.38 7.39 |
| COMMENTS | 1:14 PM 1:21 PM 1:28 PM 2:30 PM 8 Water Clear TIME 12:59 PM 1:08 PM 1:13 PM 1:19 PM 1:25 PM 2:50 PM | DEPTH TO WATER 28.88 29.57 | WELL 4964 | DIA 4 | VOL 12.45 | 13 26 39 PRG VOL 36 1 12 24 36 | 2.11 2.06 2.05 COND. 2.87 2.82 2.77 | 72.7 72.4 72.2 TEMP 72.2 71.9 71.6 | 7.36 7.38 7.39 pH 7.77 7.76 |
| WELL # MW3 SW COMMENTS | 1:14 PM 1:21 PM 1:28 PM 2:30 PM 6 Water Clean TIME 12:59 PM 1:08 PM 1:13 PM 1:19 PM 1:25 PM 2:50 PM | DEPTH TO WATER 28.88 29.57 | WELL 4964 | DIA 4 | VOL 12.45 | 13 26 39 PRG VOL 36 1 12 24 36 | 2.11 2.06 2.05 COND. 2.87 2.82 2.77 2.76 | 72.7 72.4 72.2 TEMP 72.2 71.9 71.6 71.4 | 7.36 7.38 7.39 pH 7.77 7.76 |
| WELL # WELL # WW3 WELL # | 1:14 PM 1:21 PM 1:28 PM 2:30 PM 6 Water Clean TIME 12:59 PM 1:08 PM 1:13 PM 1:19 PM 1:25 PM 2:50 PM 6 Water Clean | DEPTH TO WATER 28.88 29.57 DEPTH TO WATER | WELL 4964 DEPTH TO WELL | DIA 4 CASE DIA | VOL 12.45 CASE VOL | 13 26 39 PRG VOL 36 1 12 24 36 PRG VOL | 2.11 2.06 2.05 COND. 2.87 2.82 2.77 | 72.7 72.4 72.2 TEMP 72.2 71.9 71.6 | 7.36 7.38 7.39 pH 7.77 7.76 7.72 |
| WELL # WELL # WW3 WELL # | 1:14 PM 1:21 PM 1:28 PM 2:30 PM 6 Water Clean TIME 12:59 PM 1:08 PM 1:13 PM 1:19 PM 1:25 PM 2:50 PM 6 Water Clean TIME 1:55 PM | DEPTH TO WATER 28.88 29.57 | WELL 4964 | DIA 4 | VOL 12.45 | 13 26 39 PRG VOL 36 1 12 24 36 PRG VOL 39 | 2.11 2.06 2.05 COND. 2.87 2.82 2.77 2.76 | 72.7 72.4 72.2 TEMP 72.2 71.9 71.6 71.4 | 7.36 7.38 7.39 pH 7.77 7.76 7.72 7.74 |
| WELL # WELL # WW3 WELL # | 1:14 PM 1:21 PM 1:28 PM 2:30 PM 8 Water Clean 1:08 PM 1:08 PM 1:13 PM 1:19 PM 1:25 PM 2:50 PM Water Clean TIME 1:25 PM 2:50 PM 2:50 PM | DEPTH TO WATER 28.88 29.57 DEPTH TO WATER | WELL 4964 DEPTH TO WELL | DIA 4 CASE DIA | VOL 12.45 CASE VOL | 13 26 39 PRG VOL 36 1 12 24 36 PRG VOL 39 | 2.11 2.06 2.05 COND. 2.87 2.82 2.77 2.76 | 72.7 72.4 72.2 TEMP 72.2 71.9 71.6 71.4 | 7.36 7.38 7.39 pH 7.77 7.76 7.72 7.74 |
| WELL # WELL # WW3 WELL # | 1:14 PM 1:21 PM 1:28 PM 2:30 PM S Water Clean TIME 12:59 PM 1:08 PM 1:13 PM 1:19 PM 1:25 PM 2:50 PM Water Clean TIME 1:55 PM 2:00 PM 2:06 PM | DEPTH TO WATER 28.88 29.57 DEPTH TO WATER | WELL 4964 DEPTH TO WELL | DIA 4 CASE DIA | VOL 12.45 CASE VOL | 13 26 39 PRG VOL 36 1 12 24 36 VOL 39 1 13 | 2.11 2.06 2.05 COND. 2.87 2.82 2.77 2.76 COND. | 72.7 72.4 72.2 TEMP 72.2 71.9 71.6 71.4 TEMP 71.7 | 7.36 7.38 7.39 pH 7.77 7.76 7.72 7.74 |
| WELL # WELL # WW3 WELL # | 1:14 PM 1:21 PM 1:28 PM 2:30 PM S Water Clean TIME 12:59 PM 1:08 PM 1:13 PM 1:19 PM 1:25 PM 2:50 PM Water Clean TIME 1:55 PM 2:00 PM 2:06 PM 2:13 PM | DEPTH TO WATER 28.88 29.57 DEPTH TO WATER | WELL 4964 DEPTH TO WELL | DIA 4 CASE DIA | VOL 12.45 CASE VOL | 13 26 39 PRG VOL 36 1 12 24 36 VOL 39 1 13 26 | 2.11 2.06 2.05 COND. 2.87 2.82 2.77 2.76 COND. 2.09 2.06 2.02 | 72.7 72.4 72.2 TEMP 72.2 71.9 71.6 71.4 TEMP 71.7 71.6 71.1 | 7.36 7.38 7.39 pH 7.77 7.76 7.72 7.74 pH 7.72 7.69 7.66 |
| WELL # WW3 SW COMMENTS | 1:14 PM 1:21 PM 1:28 PM 2:30 PM S Water Clean TIME 12:59 PM 1:08 PM 1:13 PM 1:19 PM 1:25 PM 2:50 PM Water Clean TIME 1:55 PM 2:00 PM 2:06 PM | DEPTH TO WATER 28.88 29.57 DEPTH TO WATER | WELL 4964 DEPTH TO WELL | DIA 4 CASE DIA | VOL 12.45 CASE VOL | 13 26 39 PRG VOL 36 1 12 24 36 VOL 39 1 13 | 2.11 2.06 2.05 COND. 2.87 2.82 2.77 2.76 COND. | 72.7 72.4 72.2 TEMP 72.2 71.9 71.6 71.4 TEMP 71.7 | 7.36 7.38 7.39 pH 7.77 7.76 7.72 7.74 |

| <u>CLIENT NA</u> | ME: EXXO | MOBIL 18M | <u>LJ</u> | ERI JOE | 3 # 3163 13 | _ , | 0.163 FC | R A 2" W | ELL |
|-----------------------|---|--|-----------------------------|----------|----------------------|--|---|--------------------------------------|----------------------------|
| SITE LOCA | TION: 5005 | N. LONG BE | ACH BLVD | | SIS: TPHg | - | | R A 4" W | |
| | | QDATE: 3/21/ | | TPHd | | | | R A 6" W | |
| | | | Т DEPTH ТО | CASE | CASE | PRG | | | |
| WELL# | TIME | WATER | WELL | DIA | VOL | VOL | COND. | TEMP | pН |
| MW2 | 1:01 PM | 27.96 | 50.78 | 4 | 14.90 | 45 | COMB. | I LEIVII | hii |
| | 1:33 PM | | | | | 1 | 2.55 | 71,7 | 7.17 |
| | 1:41 PM | | | | | 15 | 2.48 | 71.4 | 7.19 |
| | 1:50 PM | | | | | 30 | 2.44 | 71.1 | 7.15 |
| | 1:59 PM | | | | | 45 | 2.42 | 70.8 | 7.14 |
| SW | 3:00 PM | 28.99 | | | | | | | |
| COMMENT | | | ДЕРТН ТО | CASE | CASE | PRG | 1 | | |
| WELL# | TIME | WATER | WELL | DIA | VOL | VOL | COND. | TEMP | pН |
| MW5 | 1:57 PM | 27.39 | 46.88 | 4 | 12.72 | 39 | COITD. | TENTE | PII |
| | 2:25 PM | | | | | 1 | 2.36 | 72.4 | 8.13 |
| | 0.04.014 | | | | | 13 | 2.31 | 72.1 | 8.11 |
| | 2:31 PM | | | | | | | | |
| | 2:31 PM 2:38 PM | | | | | 26 | | 71.7 | 8.06 |
| | | | | | | 26 39 | 2.29 | 71.7 71.8 | 8.06 8.04 |
| SW COMMENTS | 2:38 PM 2:45 PM 2:55 PM | 29.44 dy | | - | | | | 71.7 71.8 | 8.06 8.04 |
| | 2:38 PM 2:45 PM 2:55 PM | | ДЕРТН ТО | CASE | CASE | 39 | 2.29 | | |
| | 2:38 PM 2:45 PM 2:55 PM | dy | DEPTH TO WELL | CASE DIA | CASE VOL | | 2.29 | 71.8 | 8.04 |
| COMMENTS WELL# | 2:38 PM 2:45 PM 2:55 PM Water Cloud TIME 1:03 PM | dy DEPTH TO | | | CASE VOL 13.06 | 39 PRG | 2.29 | | |
| COMMENTS WELL# | 2:38 PM 2:45 PM 2:55 PM Water Cloud | DEPTH TO WATER | WELL | DIA | VOL | 99 PRG VOL | 2.29 | 71.8 | 8.04 |
| COMMENTS WELL# | 2:38 PM 2:45 PM 2:55 PM Water Cloud TIME 1:03 PM 1:33 PM 1:39 PM | DEPTH TO WATER | WELL | DIA | VOL | PRG VOL 39 | 2.29 2.28 COND. | 71.8 TEMP | 8.04 pH |
| COMMENTS WELL# | 2:38 PM 2:45 PM 2:55 PM Water Cloud TIME 1:03 PM 1:33 PM 1:39 PM 1:46 PM | DEPTH TO WATER | WELL | DIA | VOL | 9 PRG VOL 39 1 | 2.29 2.28 COND. | 71.8 TEMP | 8.04 рН |
| WELL# | 2:38 PM 2:45 PM 2:55 PM Water Cloud TIME 1:03 PM 1:33 PM 1:39 PM 1:46 PM 1:53 PM | DEPTH TO WATER 27.76 | WELL | DIA | VOL | 9 PRG VOL 39 1 | 2.29 2.28 COND. | 71.8 TEMP 71.1 70.9 | PH 7.71 7.66 |
| WELL # MW6 | 2:38 PM 2:45 PM 2:55 PM Water Cloud TIME 1:03 PM 1:33 PM 1:39 PM 1:46 PM 1:53 PM 3:10 PM | DEPTH TO WATER 27.76 | WELL | DIA | VOL | 39 PRG VOL 39 1 13 26 | 2.29 2.28 COND. 2.57 2.51 2.44 | 71.8 TEMP 71.1 70.9 70.3 | PH 7.71 7.66 7.61 |
| WELL # | 2:38 PM 2:45 PM 2:55 PM Water Cloud TIME 1:03 PM 1:33 PM 1:39 PM 1:46 PM 1:53 PM 3:10 PM | DEPTH TO WATER 27.76 29.16 | WELL 47.77 | DIA 4 | VOL 13.06 | 39 PRG VOL 39 1 13 26 | 2.29 2.28 COND. 2.57 2.51 2.44 | 71.8 TEMP 71.1 70.9 70.3 | pH 7.71 7.66 7.61 |
| WELL# MW6 SW COMMENTS | 2:38 PM 2:45 PM 2:55 PM Water Cloud TIME 1:03 PM 1:39 PM 1:39 PM 1:46 PM 1:53 PM 3:10 PM Water Cloud | DEPTH TO WATER 27.76 29.16 dy DEPTH TO | WELL 47.77 | DIA 4 | VOL 13.06 | 39 PRG VOL 39 1 13 26 | 2.29 2.28 COND. 2.57 2.51 2.44 | 71.8 TEMP 71.1 70.9 70.3 | PH 7.71 7.66 7.61 |
| WELL # MW6 | 2:38 PM 2:45 PM 2:55 PM Water Cloud TIME 1:03 PM 1:33 PM 1:39 PM 1:46 PM 1:53 PM 3:10 PM | DEPTH TO WATER 27.76 29.16 | WELL 47.77 | DIA 4 | VOL 13.06 | 9 PRG VOL 39 1 13 26 39 | 2.29 2.28 COND. 2.57 2.51 2.44 | 71.8 TEMP 71.1 70.9 70.3 | PH 7.71 7.66 7.61 |
| WELL# MW6 SW COMMENTS | 2:38 PM 2:45 PM 2:55 PM Water Cloud TIME 1:03 PM 1:39 PM 1:39 PM 1:46 PM 1:53 PM 3:10 PM Water Cloud | DEPTH TO WATER 27.76 29.16 dy DEPTH TO | WELL 47.77 | DIA 4 | VOL 13.06 | PRG VOL 39 1 13 26 39 | 2.29 2.28 COND. 2.57 2.51 2.44 2.41 | 71.8 TEMP 71.1 70.9 70.3 70.1 | PH 7.71 7.66 7.61 7.59 |
| WELL# MW6 SW COMMENTS | 2:38 PM 2:45 PM 2:55 PM Water Cloud TIME 1:03 PM 1:39 PM 1:39 PM 1:46 PM 1:53 PM 3:10 PM Water Cloud | DEPTH TO WATER 27.76 29.16 dy DEPTH TO | WELL 47.77 | DIA 4 | VOL 13.06 | PRG VOL 39 1 13 26 39 | 2.29 2.28 COND. 2.57 2.51 2.44 2.41 | 71.8 TEMP 71.1 70.9 70.3 70.1 | PH 7.71 7.66 7.61 7.59 |
| WELL# MW6 SW COMMENTS | 2:38 PM 2:45 PM 2:55 PM Water Cloud TIME 1:03 PM 1:39 PM 1:39 PM 1:46 PM 1:53 PM 3:10 PM Water Cloud | DEPTH TO WATER 27.76 29.16 dy DEPTH TO | WELL 47.77 | DIA 4 | VOL 13.06 | PRG VOL 39 1 13 26 39 | 2.29 2.28 COND. 2.57 2.51 2.44 2.41 | 71.8 TEMP 71.1 70.9 70.3 70.1 | PH 7.71 7.66 7.61 7.59 |
| WELL# MW6 SW COMMENTS | 2:38 PM 2:45 PM 2:55 PM Water Cloud TIME 1:03 PM 1:39 PM 1:39 PM 1:46 PM 1:53 PM 3:10 PM Water Cloud | DEPTH TO WATER 27.76 29.16 dy DEPTH TO | WELL 47.77 | DIA 4 | VOL 13.06 | PRG VOL 39 1 13 26 39 | 2.29 2.28 COND. 2.57 2.51 2.44 2.41 | 71.8 TEMP 71.1 70.9 70.3 70.1 | PH 7.71 7.66 7.61 7.59 |
| WELL# MW6 SW COMMENTS | 2:38 PM 2:45 PM 2:55 PM Water Cloud TIME 1:03 PM 1:39 PM 1:39 PM 1:46 PM 1:53 PM 3:10 PM Water Cloud | DEPTH TO WATER 27.76 29.16 dy DEPTH TO | WELL 47.77 | DIA 4 | VOL 13.06 | PRG VOL 39 1 13 26 39 | 2.29 2.28 COND. 2.57 2.51 2.44 2.41 | 71.8 TEMP 71.1 70.9 70.3 70.1 | PH 7.71 7.66 7.61 7.59 |

WELL SAMPLING & SURVEYING SOP-5

WELL SAMPLING AND SURVEYING

- Open well heads. This may require a socket or a special allen wrench. 1)
- 2) Survey the wells if this hasn't been done before as follows:
 - Select a permanent benchmark (e.g. curb at corner of site, property line). Record on a) "SURVEYGW" form.

Measure and record rectangular coordinates from benchmark to each well. b)

Set up tripod and transit where it can see all wells and the benchmark = Station "A". c) If you can't see all wells, two transit locations must be used. At least one well surveyed from Station "A" must be resurveyed from Station "B". Preferably, two or more wells d)

Carefully level the tripod using the bubble indicator.

- Place stadia rod on benchmark and record height from crosshair to reference, (Do). e) f)
- Place stadia rod on each well (at the notch) and record ht. from well to crosshair, (D_w). g)

Calculate casing elevation as shown on data sheet SURVEYGW.

To check the accuracy in leveling the transit, set the transit in second spot and repeat steps 2c through 2g. Recalculation of casing elevations should agree within 0.01 ft. or a third placement of the tripod will be required.

- 3) Decon the water level indicator before inserting into each well. Lower indicator until it beeps raise and lower and mark the level on the tape with your thumb. Estimate level to the nearest 0.01 ft. Note any odor when the probe is withdrawn from the well. Look for the notch or ink mark on the top of the well and measure all levels from that. Notch should be on the highest side of the well pipe. If no side is high, notch should be on the north side. Measure from the casing adjacent to the notch - not from the bottom of the notch. If there is no notch - make one.
- 4) After measuring all water levels, check for a sheen in each well using a bailer. If the stainless bailer is used - decon before inserting into each well. If there is a sheen, do not purge or sample. The presence of liquid phase hydrocarbons means the concentration in the water will be high anyway and the pump will be difficult to get clean enough to avoid contaminating other
- Developing: If the well has not been developed (it is new), surge the well by moving bailer up 5) and down vigorously in the well for about 5 minutes. This will wash silt from the sand pack into the well where it can be removed.
- 6) Pull out as much silt as possible by running the bailer all the way to the bottom and withdrawing. Continue bailing until water is fairly clear or until local regulatory specifications are met. Removal of silt with the bailer will extend the pump life. Contact the Project Manager if water does not clear up by 10 casing volumes.
- Decon pump by washing in TSP/water the rinsing with tap water and rinsing again with deionized 7) water. Then pump clean water through the pump to push out any dirty water.

- Purging: Place pump in well about 2 to 5 feet off bottom. Withdraw at least 3 casing volumes from the well, or until temperature, pH and conductivity stabilize (see local regulations). Be careful not to let the pump run dry. Check level with the water level indicator and slow pump down when water level is within 2 ft of the pump head. While purging, collect a water sample as often as possible and check for pH, conductivity, and temperature. Stable pH and conductivity would indicate the well has been filled with representative groundwater and purging is complete. If well recharges slowly, remove 1.5 casing volumes. Estimate flow rates by recording the time it takes to fill a 5-gallon bucket (1/2 of a 55-gallon barrel, etc.)
- 9) Decon pump thoroughly between each well by repeating step 7.
- Label bottles with a "Sharpie Pen" when they are dry. Label as W-xx-MWy, where xx is water depth below surface in feet and y is well number (refer to SOP-1).
- After the well has been developed, sample the water using a disposable bailer and surgical gloves to prevent oil from your hands from contaminating the sample. Be sure to leave no headspace or bubbles in any water sample to be tested for volatiles. Wells should be sampled within (24) hours of purging and the well should have recovered to within 80% of its volume before purging. (Slow recharge wells need to be addressed with the Project Manager and may have to be purged slowly). Gasoline contaminated water requires 2 x 40 ml VOA's from each well. Preserve samples by acidifying to pH <2 (usually with two drops of HCl). Water suspected of contamination with oil or diesel requires 2 1-liter samples in amber bottles. Samples require 2 1-liter amber bottles.
- Place like vials in a baggie and label the baggie. Put vials and baggie in an ice chest and document samples and analyses required on a chain of custody. Take samples to the laboratory the same day samples are collected if possible, at least within 24 hours.
- Clean wellhead gaskets (seals), put locking caps on the wells and replace the covers. Cover and label the drums (if any) of purge and decon water.

| Analysis | Bottles | Preservative |
|---|---|---|
| 8015 mod gasoline/8020(602) 8015 mod diesel/8020(602) 418.1 (TRPH) Organic Lead HOC - 8010 (601) | 2 x 40 ml VOA 2 1-liter & 2 x 40 ml VOA 2 1-liter amber 2 1-liter amber 2 x 40 ml VOA | 2 drops HCl to pH <2 2 drops HCl to pH <2 (applied to VOA's) 10 drops H ₂ SO ₄ to pH <2 no preservative suggested no preservative suggested |
| Items Needed: Water Level Indicator Bailer Generator Grundfos Pump and Reel Grundfos Pump Control Box Hydac Cond/Temp/pH Meter Liter Bottles VOAs | Distilled Water 3 Buckets Bottle Brush TSP Detergent Stainless Steel Cable or Poly Cooler with Ice Socket set and Allen Wrench Plastic sheeting | • |

QUARTERLY WELL MONITORING SOP-6

QUARTERLY WELL MONITORING

- 1) Give the site manager advance notification of field activities. Arrange for a sufficient number of drums. Obtain a site plan with the location and ID's of the wells to be monitored and a copy of the table from the last quarterly report with the previous groundwater data.
- 2) Open well heads. This may require a socket or a special allen wrench.
- Measure groundwater depths with water level indicator as per SOP-5 before any other action is taken. If the depth to the bottom of the monitoring well is unknown, reel out the water level indicator until you feel the probe contact the bottom. You may have to raise and lower the probe several times to "feel" contact with the bottom. The probe is not very heavy, and the bottom of the well may have a cushioning layer of silt. Record the depth of the well once you feel confident the probe is at the bottom. Note odors from well.
- Calculate the linear footage of water in each well, by subtracting the depth to water from the total well depth. To obtain the casing volume in gallons, multiply the linear footage by a constant for the given well casing diameter. Typically, three casing volumes are purged from each well prior to sampling. Always Round up if 3.4 gallons, then purge 4 gallons if 12.1 gallons, then purge 13 gallons.

| Casing diameter | Gallons per linear foot |
|-----------------|-------------------------|
| 2 | 0.17 |
| 4" 6" | 0.66 |
| 8" | 1.50 |
| o | 2.60 |

- After measuring all water levels, begin purging the wells in order of the cleanest to the most contaminated based on last quarter's data. Well purging procedures are outlined in SOP-5. While wells containing free floating product may not be sampled, the project manager may want the free product removed manually by bailer. Check with the project manager before bailing LPH. You may find that for shallow wells, it may be quicker to bail manually rather than set up the pump. Place purge and decon water in a 55-gallon drum or treat on site. Do not mix purge water from different wells in one drum. Record all purge data on Groundwater Sampling Field Logs. Record "LPH" and the thickness in feet and inches (to nearest 1/16 of an inch) in the comments section if a measurable level of LPH present. If non-measurable amount present then record "Sheen" in the comments section.
- When the well has recovered at least 80% of its' original water level, collect samples using a clean bailer. Make sure the rope is tied securely on the bailer, you don't want to go fishing. Sample in order of the cleanest to the most contaminated. If required, collect field (equipment) blanks.
- Trip blanks are a QA/QC procedure that must be collected at every site. Obtain a trip blank from the laboratory. They will make them up for you. The trip blank to taken unopened to the site and is kept with the other samples in the cooler unopened during the day's sampling. Label the bottle as an arbitrary monitoring well. For example: if there are 5 monitoring wells to be sampled at the site, the trip blank should be labeled as if it were a sample from MW6. The trip blank is never opened and it is used to determine if any contaminants are introduced by the laboratory or during transportation of the samples.
- Field (equipment) blanks are a QA/QC procedure to be collected at the project manager's discretion (or always for LACDPW sites). To collect a field blank decon a bailer thoroughly; pour distilled water into the bailer; pour the distilled water from the bailer into appropriate

sample bottle(s) for the analysis to be performed, allow for no headspace; label the bottle as an arbitrary monitoring well. For example: if there are 5 monitoring wells to be sampled at the site plus a trip blank, and a field blank is to collected, the field blank should be labeled as if it were a sample from MW7 (the trip blank is MW6). If a disposable bailer is used for sampling, use a new disposable bailer to collect the field blank.

- 9) Label sample containers when they are dry (refer to SOP-1). Place vials from each well in a separate plastic ziplock bag and label the bag. Put bag in an ice chest and document samples and analyses required on a chain of custody (see attached examples).
- Replace the locking caps, and the covers. Cover and label the drums of waste water. Place the drums on site in a location selected by the site manager. Usually, this will be near a dumpster or in the back, away from public view. Labels should face outward.
- 11) Decon all equipment before leaving the site.

In general, groundwater sampling will be performed in accordance with LUFT guidelines. Several local agencies require that groundwater sampling occur under slightly different guidelines. Check with the project manager to find out which sites require special groundwater sampling procedures. Typically, the following apply:

Orange County Health Care Agency Requirements

No special requirements. Water sampling will be performed as per the State Water Resources Board's LUFT manual.

LARWOCB Groundwater Requirements

- Purge a minimum of four well volumes if recovery is fast, or one borehole volume if recovery is slow (water does not recover to 80% of original level within two hours).
- The last three readings must be within 10% for conductivity, temperature, and pH to show stabilization. This means that all three consecutive readings must be within these limits the first with the middle, and the first with the last, and the middle with the last. For instance, pH readings of 6.92, 6.95, and 7.00 would be sufficient.
- Even though there are no guidelines for turbidity, the measurements should be less than 10 NTU, or meet the baseline level established during development, upon completion of purging. Check with project manager if you use the baseline turbidity level.
- Prior to sampling document recovery time by measuring the water level in each well to prove that at least 80% recovery has occurred.
- o A trip blank must be collected.
- O In the comments column of the chain of custody, write " Prepare laboratory report in WIP format."

San Diego Department of Health Services Groundwater Sampling Requirements

- SDDHS does not encourage purging wells until dry.
- Purge one borehole volume of water if recovery is fast, collecting pH/temperature/conductivity measurements while purging, then remove an additional one-half borehole volume of water. If the first and second measurements vary by less than 10%, purging is considered adequate. If not,

keep purging water in one-half borehole volume increments until the measurements vary by less than 10%, or three borehole volumes have been removed. Obtain three consecutive pH/temperature/conductivity measurements that are within 10% of each other.

- o If recovery is slow (water does not recover to 80% of original level within two hours) purge only one borehole volume of water.
- Prior to sampling document recovery time by measuring the water level in each well to prove that at least 80% recovery has occurred.

Ventura County Environmental Health Division Groundwater Sampling Requirements

- o A trip blank and a duplicate sample must be analyzed for each site.
- o Custody seals must be place over the cap of each sample.

Under certain conditions the calculated purge volumes will need to be calculated in borehole volumes instead of well casings volumes. Use the following to calculate borehole volume in gallons.

Well I.D.

2"

0.90 gal/ft. in water

4"/or nested wells

1.70 gal/ft. in water

The completed groundwater sampling log must contain:

- pH/temp./conductivity and turbidity measurements indicating stabilization

- time and volume of water removed at each pH/temp./conductivity measurements

- total volume of water purged

- name of personnel performing sampling

- date and project number

- problems or unusual conditions arising during purging or sampling, such as the well going dry during purging, water in the well vault, missing well caps or locks, odors, appearance of purge water, etc.
- 80% recovery measurement and time of measurement after purging and before sampling

All chains of custody for the client's groundwater sites must contain the consultant work release number, station identification number and client contact among the other items to be filled out. Check the groundwater sampling field log and chain of custody for completeness, accuracy and neatness. If you have any questions, call!!!

Make sure that the date and time of relinquished and accepted at the lab are the same on the chain of custody. Also, make sure the lab fills in the sample condition information and signs for the samples on the chain of custody

Santa Barbara County Environmental Health Services Groundwater Monitoring Guidelines

I. Groundwater Monitoring

A. Groundwater levels are to be monitored/measured in all wells in a short timespan.

B. Measure the groundwater levels (correct for "free product" thickness).

C. Use a clear bailer to check for the presence of "floating product," sheen, and odors.

D. Replace well cover until ready to purge well.

II. Purging

- A. Amount: generally 3 to 5 (no more than 10) well volumes; via bailer, pumps, or vacuum truck.
- B. Parameters (pH, temperature, conductivity) shall stabilize while purging.
 - 1. Measure the parameters of a small volume (i.e., a 500 ml) of the water as it is removed from the well. Measure the parameters initially and at regular volume intervals (e.g., after every well casing volume). More frequent testing may be needed if the well is known to go dry.
 - 2. Wells must be allowed to recharge prior to sampling (see section G of the Santa Barbara County LUFT Manual).
- C. Slow recharging wells are wells that are purged dry before removing 3 well volumes of water, and take more than **two (2)** hours to recharge.
 - 1. Note this on the field records and estimate the number of well volumes removed.
 - 2. Allow the well to recharge a minimum of two (2) feet and then sample.
 - 3. Sample wells no later than 24 hours after purging.
 - 4. Note the water level and percentage of recharge in the report.

III. Sample Collection

- A. Use either a decontaminated teflon, stainless steel, or disposable bailer.
- B. Sample containers are to be supplied and certified by a laboratory:
 - 1. VOAs of 40 ml volume (2 per well); fill VOAs first to reduce volatization.
 - 2. 4 oz sample containers for Pb (metallic lead) analysis (if needed).
- C. Fill containers by pouring along the inside of the vial to reduce volatilization.
- D. Form a positive meniscus with the water, to avoid trapping air, before placing the cap on the VOA. Samples with headspace are not acceptable for analysis.
 - 1. Check for bubbles by inverting and tapping gently to dislodge bubbles.
 - 2. If bubbles are found, uncap and repeat steps C and D.
- E. Label all samples and store immediately in an ice chest at 4 degrees celsius (blue ice).
- F. Be careful to properly decontaminate equipment between each and every well.